2000 Tow Ratings

Compiled by Doug Marion

Trailer Life's annual guide to factory tow ratings for autos, light-duty trucks, sport-utility vehicles and vans is the largest guide ever published. Minimum vehicle towing capacity is 2,000 pounds. While the respective manufacturers provide all the specifications—and every effort has been taken to ensure accuracy—buyers should verify the information by reading the factory tow guide for their particular vehicle. It's also important to note that some capacities may change during the model year without notice, and a few were not available at presstime. Again, consult with the latest towing guide for your respective vehicle manufacturer before signing on the dotted line.

2000

NOTE: Vehicles with tow ratings that are below 2,000 pounds are not included.

AM GENERAL

Vehicle	Engine	Tow Limit (lbs.)
Hummer 2dr Hardtop	6.5 TD	8,300
Hummer 4dr Open Top	6.5 TD	8,050
Hummer 4dr Hardtop	6.5 TD	7,900
Hummer Station Wagon	6.5 TD	7,710

TD = Turbodiesel

CADILLAC

Vehicle	Engine	Tow Limit (lbs.)
Deville	4600 V-8	3,000[a]
Seville	4600 V-8	3,000[a]
Escalade	5700 V-8	6,600[a]

[a]Requires trailer-towing package.

CHEVROLET/GMC

Vehicle	Engine	Tow Limit (lbs.)
Astro/Safari RWD	4300 V-6	5,100[a,h]
Astro/Safari RWD	4300 V-6	5,600[b,h]
Astro/Safari RWD	4300 V-6	6,100[c,h]
Astro/Safari AWD	4300 V-6	5,300[b,h]
Astro/Safari AWD	4300 V-6	5,800[c,h]
Express/Savana G1500	4300 V-6	4,900[b]
Express/Savana G1500	4300 V-6	5,400[c,h]
Express/Savana G2500	4300 V-6	4,700[b]
Express/Savana G2500	4300 V-6	5,400[d,h]
Express/Savana G1500	5000 V-8	5,800[b,h]
Express/Savana G2500	5000 V-8	5,600[b,h]
Express/Savana G1500	5700 V-8	6,300[b,h]
Express/Savana G1500	5700 V-8	7,300[c,h]
Express/Savana G2500	5700 V-8	6,100[b,h]
Express/Savana G2500	5700 V-8	7,100[c,h]
Express/Savana G2500	5700 V-8	8,300[d,h]
Express/Savana G3500	5700 V-8	6,600[c,h]
Express/Savana G3500	5700 V-8	8,100[d,h]
Express/Savana G2500	6.5 TD	8,900[c/d,h]
Express/Savana G3500	6.5 TD	8,800[c/d,h]
Express/Savana G3500	7400 V-8	7,900[b,h]
Express/Savana G3500	7400 V-8	9,400[c,h]
Express/Savana G3500	7400 V-8	10,000[d,h]
Blazer/Jimmy	4300 V-6	4,900[e,f]
Blazer/Jimmy	4300 V-6	5,900[b,f,h]
Blazer/Jimmy	4300 V-6	4,400[b,g]
Blazer/Jimmy 4WD	4300 V-6	4,600[e,f]
Blazer/Jimmy 4WD	4300 V-6	5,600[b/c,f,h]
Blazer/Jimmy 4WD	4300 V-6	4,000[b,g]
Blazer/Jimmy 4WD	4300 V-6	4,500[c,g]
S-10/Sonoma	2200 I-4	2,000[c,g]
S-10/Sonoma	2200 I-4	2,300[d,g]
S-10/Sonoma	2200 I-4	3,200[d,f]
S-10/Sonoma	4300 V-6	5,400[e,f,h]
S-10/Sonoma	4300 V-6	6,400[b,f,h]
S-10/Sonoma 4WD	4300 V-6	4,900[e,f]
S-10/Sonoma 4WD	4300 V-6	5,900[b/c,f,h]
S-10/Sonoma	4300 V-6	4,200[e,g]
S-10/Sonoma 4WD	4300 V-6	3,900[e,g]
S-10/Sonoma 4WD	4300 V-6	4,400[b,g]
S-10/Sonoma 4WD	4300 V-6	4,900[c,g]
Silverado/Sierra 1500	4300 V-6	3,900[e,g]
Silverado/Sierra 1500	4300 V-6	4,400[b,g]
Silverado/Sierra 1500	4300 V-6	4,900[e,f]
Silverado/Sierra 1500	4300 V-6	5,400[b,f,h]
Silverado/Sierra 1500	4300 V-6	5,900[c,f,h]
Silverado/Sierra 1500 4WD	4300 V-6	5,100[b,f,h]
Silverado/Sierra 1500 4WD	4300 V-6	5,600[c,f,h]
Silverado/Sierra 1500 4WD	4300 V-6	4,100[b,g]
Silverado/Sierra 1500 4WD	4300 V-6	4,600[c,g]
Silverado/Sierra 1500	4800 V-8	4,800[b,g]
Silverado/Sierra 1500	4800 V-8	6,800[b,f,h]
Silverado/Sierra 1500	4800 V-8	5,800[c,g,h]
Silverado/Sierra 1500	4800 V-8	7,800[c,f,h]
Silverado/Sierra 1500 4WD	4800 V-8	5,500[c,g,h]
Silverado/Sierra 1500 4WD	4800 V-8	7,500[c,f,h]
Silverado/Sierra 1500 4WD	4800 V-8	6,500[d,g,h]
Silverado/Sierra 1500 4WD	4800 V-8	8,500[d,f,h]
Silverado/Sierra 1500	5300 V-8	7,800[b,f,h]
Silverado/Sierra 1500	5300 V-8	8,800[c,f,h]
Silverado/Sierra 1500 4WD	5300 V-8	8,500[c,f,h]
Silverado/Sierra 1500 4WD	5300 V-8	9,500[d,f,h]
Silverado/Sierra 2500 LD	5300 V-8	7,400[b,f,h]
Silverado/Sierra 2500 LD	5300 V-8	8,400[c,f,h]
Silverado/Sierra 2500 LD	5300 V-8	9,400[d,f,h]
Silverado/Sierra 2500 LD	6000 V-8	9,200[c,f,h]
Silverado/Sierra 2500 LD	6000 V-8	11,200[d,h,i]
Silverado/Sierra 2500 HD	6000 V-8	9,200[c,h,i]
Silverado/Sierra 2500 HD 4WD	6000 V-8	8,800[c,h,i]
Silverado/Sierra 2500 HD 4WD	6000 V-8	10,800[d,h,i]
C/K Classic Sierra, Conventional Towing:		
2500	5700 V-8	7,100[c,h,i]
2500	5700 V-8	8,600[d,h,i]
2500 4WD	5700 V-8	6,800[c,h,i]
2500 4WD	5700 V-8	8,300[d,h,i]
2500	6.5 TD	9,300[c/d,h,i]
2500 4WD	6.5 TD	9,000[c/d,h,i]
2500	7400 V-8	9,900[c,h,i]
2500	7400 V-8	10,000[d,h,i]
2500 4WD	7400 V-8	9,500[c,h,i]
2500 4WD	7400 V-8	10,000[d,h,i]
3500	5700 V-8	8,600[d,h,i]
3500	5700 V-8	10,000[h,i,j]
3500 4WD	5700 V-8	8,300[d,h,i]
3500	6.5 TD	9,300[d,h,i]
3500 4WD	6.5 TD	9,000[d,h,i]
3500 HD	6.5 TD	10,000[h,i,k]
3500 Chassis Cab	6.5 TD	10,000[h,i,l]
3500	7400 V-8	10,000[d,h,i]
3500	7400 V-8	10,000[j,h,i]
3500 4WD	7400 V-8	10,000[d,h,i]
3500 4WD Chassis Cab	7400 V-8	10,000[h,i,k/l]
C/K, Classic Sierra, Fifth-Wheel Towing:		
2500	5700 V-8	7,100[c,i]
2500	5700 V-8	8,600[d,i]
2500 4WD	5700 V-8	6,800[c,i]
2500 4WD	5700 V-8	8,300[d,i]
2500	6.5 TD	9,300[c/d,i]
2500 4WD	6.5 TD	9,000[c/d,i]
2500	7400 V-8	9,900[c,i]
2500	7400 V-8	11,900[d,i]
2500 4WD	7400 V-8	9,500[c,i]
2500 4WD	7400 V-8	11,500[d,i]
3500	5700 V-8	8,600[d,i]
3500	5700 V-8	10,000[j,i]
3500 4WD	5700 V-8	8,300[d,i]
3500	6.5 TD	9,300[d,i]
3500 4WD	6.5 TD	9,000[d,i]
3500 HD	6.5 TD	11,000[k/l,i]
3500	7400 V-8	11,800[d,i]
3500	7400 V-8	13,800[j,i]
3500 4WD	7400 V-8	11,500[d,i]
3500 4WD	7400 V-8	13,500[j,i]
3500 HD Chassis Cab	7400 V-8	13,000[k/l,i]
Tahoe/Yukon 1500	4800 V-8	6,100[b,f,h]
Tahoe/Yukon 1500	4800 V-8	7,100[c,f,h]
Tahoe/Yukon 1500 4WD	4800 V-8	6,800[b,f,h]
Tahoe/Yukon 1500 4WD	4800 V-8	7,800[d,f,h]
Tahoe/Yukon 1500	5300 V-8	7,100[b,f,h]
Tahoe/Yukon 1500	5300 V-8	8,100[c,f,h]
Tahoe/Yukon 1500 4WD	5300 V-8	7,800[b,f,h]
Tahoe/Yukon 1500 4WD	5300 V-8	8,800[d,f,h]
Yukon Denali	5700 V-8	6,600[c,f,h]
Suburban/Yukon XL 1500	5300 V-8	8,000[c,f,h]
Suburban/Yukon XL 1500	5300 V-8	9,000[d,f,h]
Suburban/Yukon XL 1500 4WD	5300 V-8	7,800[b,f,h]
Suburban/Yukon XL 1500 4WD	5300 V-8	8,800[d,f,h]
Suburban/Yukon XL 2500	6000 V-8	8,500[b,f,h]
Suburban/Yukon XL 2500	6000 V-8	10,500[d,f,h]
Suburban/Yukon XL 2500 4WD	6000 V-8	8,100[b,f,h]
Suburban/Yukon XL 2500 4WD	6000 V-8	10,100[d,f,h]
Venture	3400 V-6	3,500[h]

LD = Light Duty HD = Heavy Duty TD = Turbodiesel

[a]Requires 3.23:1 axle ratio.
[b]Requires 3.42:1 axle ratio.
[c]Requires 3.73:1 axle ratio.
[d]Requires 4.10:1 axle ratio.
[e]Requires 3.08:1 axle ratio.
[f]Requires automatic transmission.
[g]Requires manual transmission.
[h]Requires heavy-duty tow package.
[i]Requires automatic or manual transmission.
[j]Requires 4.56:1 axle ratio.
[k]Requires 4.63:1 axle ratio.
[l]Requires 5.13:1 axle ratio.

CHRYSLER

Vehicle	Engine	Tow Limit (lbs.)
Concorde, 300M, LHS	3.2 V-6	2,000[a]
300M, LHS	3.5 V-6	2,000[a]
Town & Country Van	3.3, 3.8 V-6	3,500[a,b]

[a]Requires trailer-towing package.
[b]Requires a Class II load-equalizing hitch.

DODGE

Vehicle	Engine	Tow Limit (lbs.)
Dakota	2.5 I-4	2,250[a,g]
Dakota	3.9 V-6	5,050[b,d]
Dakota	3.9 V-6	4,300[d,g]
Dakota	3.9 V-6	5,450[a,b]
Dakota	3.9 V-6	3,800[g,h]
Dakota	4.7 V-8	5,600[d,g]
Dakota	4.7 V-8	6,600[a,g]
Dakota	4.7 V-8	5,250[c,d]
Dakota	4.7 V-8	6,550[a,c]
Dakota R/T	5.9 V-8	2,000[a,b]
Dakota R/T Club Cab	5.9 V-8	2,000[a,b]
Dakota 4WD	3.9 V-6	4,000[d,g]
Dakota 4WD	3.9 V-6	4,800[a,g]
Dakota 4WD	3.9 V-6	5,200[a,b]
Dakota 4WD	4.7 V-8	5,400[d,g]
Dakota 4WD	4.7 V-8	6,400[a,g]
Dakota 4WD	4.7 V-8	6,350[a,b]
Dakota 4WD	4.7 V-8	5,050[b,d]
Dakota Club Cab	2.5 I-4	2,050[a,g]
Dakota Club Cab	3.9 V-6	3,550[g,h]
Dakota Club Cab	3.9 V-6	4,050[d,g]
Dakota Club Cab	3.9 V-6	4,850[a,g]
Dakota Club Cab	3.9 V-6	4,800[b,d]
Dakota Club Cab	3.9 V-6	5,200[a,b]
Dakota Club Cab	4.7 V-8	5,500[d,g]
Dakota Club Cab	4.7 V-8	6,500[a,g]
Dakota Club Cab	4.7 V-8	5,100[c,d]
Dakota Club Cab	4.7 V-8	6,400[a,c]
Dakota Club Cab 4WD	3.9 V-6	3,800[d,g]
Dakota Club Cab 4WD	3.9 V-6	4,600[a,g]
Dakota Club Cab 4WD	3.9 V-6	5,000[a,b]
Dakota Club Cab 4WD	4.7 V-8	5,200[d,g]
Dakota Club Cab 4WD	4.7 V-8	6,200[a,g]
Dakota Club Cab 4WD	4.7 V-8	4,850[b,d]
Dakota Club Cab 4WD	4.7 V-8	6,150[a,b]
Dakota Quad Cab	3.9 V-6	3,250[g,h]
Dakota Quad Cab	3.9 V-6	3,750[d,g]
Dakota Quad Cab	3.9 V-6	4,550[a,g]
Dakota Quad Cab	3.9 V-6	4,500[b,d]
Dakota Quad Cab	3.9 V-6	4,900[a,b]
Dakota Quad Cab	4.7 V-8	5,150[d,g]
Dakota Quad Cab	4.7 V-8	6,150[a,g]
Dakota Quad Cab	4.7 V-8	4,800[c,d]
Dakota Quad Cab	4.7 V-8	6,100[a,c]
Dakota Quad Cab	5.9 V-8	4,750[b,d]
Dakota Quad Cab	5.9 V-8	6,350[a,b]
Dakota Quad Cab 4WD	3.9 V-6	3,450[d,g]
Dakota Quad Cab 4WD	3.9 V-6	4,250[a,g]
Dakota Quad Cab 4WD	3.9 V-6	4,650[a,b]
Dakota Quad Cab 4WD	4.7 V-8	4,900[d,g]
Dakota Quad Cab 4WD	4.7 V-8	5,900[a,g]
Dakota Quad Cab 4WD	4.7 V-8	4,800[b,d]
Dakota Quad Cab 4WD	4.7 V-8	5,800[a,b]
Dakota Quad Cab 4WD	5.9 V-8	4,500[b,d]
Dakota Quad Cab 4WD	5.9 V-8	6,100[a,b]
Durango	4.7 V-8	4,750[b,d]
Durango	4.7 V-8	6,050[a,b]
Durango	5.2 V-8	4,700[b,d]
Durango	5.2 V-8	6,000[a,b]
Durango	5.9 V-8	5,950[b,d]
Durango	5.9 V-8	7,650[a,b]
Durango 4WD	4.7 V-8	4,450[b,d]
Durango 4WD	4.7 V-8	5,750[a,b]
Durango 4WD	5.9 V-8	5,650[b,d]
Durango 4WD	5.9 V-8	7,350[a,b]
Intrepid	All	2,000
Ram Van 1500:		
109/127" Wheelbase	3.9 V-6	8,800[c,d]
109" Wheelbase	5.2 V-8	10,000[b,d]
109" Wheelbase	5.2 V-8	10,500[a,b]
127" Wheelbase	5.2 V-8	11,500[b,d]
127" Wheelbase	5.2 V-8	12,500[a,b]
127" Wheelbase	5.9 V-8	12,000[b,d]
127" Wheelbase	5.9 V-8	13,000[a,b]
Ram Van 2500/3500:		
127" Wheelbase	5.2 V-8	12,500[a,b]
127" Wheelbase	5.2 V-8	13,000[b,e]
127" Wheelbase	5.9 V-8	13,000[a,b]
127" Wheelbase	5.9 V-8	13,500[b,e]
Ram Trucks:		
1500	3.9 V-6	3,300[b,d]
1500	5.2 V-8	5,000[d,g]
1500 4WD	5.2 V-8	4,650[d,g]
1500	5.2/5.9 V-8	7,950[a/d,b]
1500 4WD	5.2 V-8	5,150[a,g]
1500 4WD	5.2 V-8	7,600[a/d,b]
1500 4WD	5.9 V-8	7,450[a,b,d]
1500 Club & Quad Cab	5.2 V-8	4,650[g,j]
1500 Club & Quad Cab	5.2/5.9 V-8	7,650[b,j]
1500 Club & Quad Cab 4WD	5.2 V-8	4,300[d,g]
1500 Club & Quad Cab 4WD	5.2 V-8	4,800[a,g]
1500 Club & Quad Cab 4WD	5.2/5.9 V-8	7,250[b,j]
2500	5.9 V-8	8,800[f,g]
2500	5.9 V-8	8,900[b,f]
2500	5.9 TD	14,150[f,i]
2500	5.9 TD	10,200[b,d]
2500	5.9 TD	12,200[b,e]
2500	8.0 V-10	13,350[f,g]
2500	8.0 V-10	13,400[b,f]
2500 4WD	5.9 V-8	8,350[f,g]
2500 4WD	5.9 V-8	8,400[b,f]
2500 4WD	5.9 TD	13,700[f,i]
2500 4WD	5.9 TD	9,750[b,d]
2500 4WD	5.9 TD	11,750[b,e]
2500 4WD	8.0 V-10	12,950[f,g]
2500 4WD	8.0 V-10	13,000[b,f]
2500 Club & Quad Cab	5.9 V-8	8,500[g,f]
2500 Club & Quad Cab	5.9 V-8	8,600[b,f]
2500 Club & Quad Cab	5.9 TD	13,850[f,i]
2500 Club & Quad Cab	5.9 TD	9,900[b,d]
2500 Club & Quad Cab	5.9 TD	11,900[b,e]
2500 Club & Quad Cab	8.0 V-10	13,150[f,g]
2500 Club & Quad Cab	8.0 V-10	13,200[b,f]
2500 Club & Quad Cab 4WD	5.9 V-8	8,050[f,g]
2500 Club & Quad Cab 4WD	5.9 V-8	8,150[b,f]
2500 Club & Quad Cab 4WD	5.9 TD	9,400[d,i]
2500 Club & Quad Cab 4WD	5.9 TD	11,400[e,i]
2500 Club & Quad Cab 4WD	5.9 TD	9,450[b,d]
2500 Club & Quad Cab 4WD	5.9 TD	11,450[b,e]
2500 Club & Quad Cab 4WD	8.0 V-10	12,650[g,f]
2500 Club & Quad Cab 4WD	8.0 V-10	12,700[b,f]
3500	5.9 V-8	9,400[f,g]
3500	5.9 V-8	9,450[b,f]
3500	5.9 TD	13,900[f,i]
3500	5.9 TD	9,950[b,d]
3500	5.9 TD	11,950[b,e]
3500	8.0 V-10	13,100[f,g]
3500	8.0 V-10	13,150[b,f]
3500 4WD	5.9 V-8	8,950[f,g]
3500 4WD	5.9 V-8	9,000[b,f]
3500 4WD	5.9 TD	13,450[f,i]
3500 4WD	5.9 TD	9,450[b,d]
3500 4WD	5.9 TD	11,450[b,e]
3500 4WD	8.0 V-10	12,700[b/g,f]
3500 Club & Quad Cab	5.9 V-8	9,100[g,f]
3500 Club & Quad Cab	5.9 V-8	9,200[b,f]
3500 Club & Quad Cab	5.9 TD	13,450[f,i]
3500 Club & Quad Cab	5.9 TD	9,500[b,d]
3500 Club & Quad Cab	5.9 TD	11,500[b,e]
3500 Club & Quad Cab	8.0 V-10	12,700[f,g]
3500 Club & Quad Cab	8.0 V-10	12,750[b,f]
3500 Club & Quad Cab 4WD	5.9 V-8	8,650[f,g]
3500 Club & Quad Cab 4WD	5.9 V-8	8,750[b,f]
3500 Club & Quad Cab 4WD	5.9 TD	13,000[d,i]
3500 Club & Quad Cab 4WD	5.9 TD	12,900[e,i]
3500 Club & Quad Cab 4WD	5.9 TD	9,050[b,d]
3500 Club & Quad Cab 4WD	5.9 TD	11,050[b,e]
3500 Club & Quad Cab 4WD	8.0 V-10	12,200[g,f]
3500 Club & Quad Cab 4WD	8.0 V-10	12,300[b,f]
Stratus	2.5 V-6	2,000

NOTE: Tow ratings over 10,000 pounds are for fifth-wheels (except vans).

TD = Turbodiesel.

[a]Requires 3.9:1 axle ratio.
[b]Requires four-speed automatic overdrive transmission.
[c]Requires three-speed automatic transmission.
[d]Requires 3.55:1 axle ratio.
[e]Requires 4.09/4.10:1 axle ratio.
[f]Requires either 3.5/3.9/4.09/4.10:1 axle ratio.
[g]Requires five-speed manual transmission.
[h]Requires 3.21:1 axle ratio.
[i]Requires manual five/six-speed transmission.
[j]Requires 3.55/3.92:1 axle ratio

FORD

Vehicle	Engine	Tow Limit (lbs.)
Crown Victoria	4.6 V-8	2,000
Econoline Van E-150	4.2 V-6	5,100[c]
Econoline Van E-250	4.2 V-6	5,200[d]
Econoline Van E-250	4.2 V-6	5,700[e]
Econoline Van E-150	4.6 V-8	6,600[c]
Econoline Wagon E-150	4.6 V-8	6,100[c]
Econoline Van E-150	5.4 V-8	6,900[c]
Econoline Wagon E-150	5.4 V-8	6,500[c]
Econoline Van E-250	5.4 V-8	7,500[d]
Econoline Van E-250	5.4 V-8 NGV	4,500[d]
Econoline Van E-350	5.4 V-8	6,500[c]
Econoline Wagon E-350	5.4 V-8	6,000[c]
Econoline Van E-350	5.4 V-8	7,500[e]
Econoline Wagon E-350	5.4 V-8	7,000[e]
Econoline Van E-350	5.4 V-8 NGV	5,000[e]
Econoline Van E-350	6.8 V-10	9,300[d]
Econoline Van E-350	6.8 V-10	10,000[e]
Econoline Wagon E-350	6.8 V-10	8,900[d]
Econoline Wagon E-350 extd	6.8 V-10	8,600[d]
Econoline Wagon E-350 extd	6.8 V-10	10,000[e]
Econoline Van E-350	7.3 TD	10,000[c/e]
Econoline Wagon E-350	7.3 TD	9,500[c]
Econoline Wagon E-350 extd	7.3 TD	9,200[c]
Econoline Van E-350 extd	7.3 TD	9,800[c]
Econoline Wagon E-350	7.3 TD	9,500[c]
Econoline Wagon E-350 extd	7.3 TD	9,200[c]
Econoline Van/Wgn E-350	7.3 TD	10,000[e]
Excursion	5.4 V-8	6,200[d]
Excursion 4WD	5.4 V-8	7,300[e]
Excursion	6.8 V-10	10,000[d]
Excursion 4WD	6.8 V-10	9,700[d]
Excursion/All	7.3 TD	10,000[d]
Expedition	4.6 V-8	5,900[b]
Expedition 4WD	4.6 V-8	5,500[c,h]
Expedition 4WD	4.6 V-8	6,000[c,g]
Expedition	5.4 V-8	6,800[b]
Expedition 4WD	5.4 V-8	6,400[b]
Expedition	5.4 V-8	7,800[c,h]
Expedition 4WD	5.4 V-8	7,400[c,g]
Expedition 4WD	5.4 V-8	6,900[c,h]
Expedition	5.4 V-8	8,300[d,g]
Explorer, Manual Transmission:		
Explorer	4.0 V-6	2,200[i]
Explorer 4dr	4.0 V-6	2,000[i]
Explorer 4WD	4.0 V-6	2,000[i]
Explorer 4WD	4.0 V-6	2,500[c]
Explorer 4WD 4dr	4.0 V-6	2,300[c]
Explorer	4.0 V-6	3,200[d]
Explorer 4dr	4.0 V-6	3,000[d]
Explorer 4WD	4.0 V-6	3,000[d/e]
Explorer 4WD 4dr	4.0 V-6	2,800[d]
Explorer, Automatic Transmission:		
Explorer	4.0 V-6	4,160[c,f]
Explorer 4dr	4.0 V-6	3,960[c,f]
Explorer	4.0 V-6	5,160[d,f]
Explorer 4dr	4.0 V-6	4,960[d,f]
Explorer 4WD	4.0 V-6	4,960[d/e,f]
Explorer 4WD 4dr	4.0 V-6	4,760[d,f]
Explorer	SOHC 4.0 V-6	3,640[i]
Explorer 4WD	SOHC 4.0 V-6	3,440[i]
Explorer	SOHC 4.0 V-6	4,640[c,f]
Explorer 4WD	SOHC 4.0 V-6	4,440[c,f]
Explorer 4dr	SOHC 4.0 V-6	4,940[c,f]
Explorer 4WD 4dr	SOHC 4.0 V-6	4,740[c,f]
Explorer	SOHC 4.0 V-6	5,140[d,f]
Explorer 4WD	SOHC 4.0 V-6	4,940[d/e,f]
Explorer 4dr	SOHC 4.0 V-6	5,940[d/e,f]
Explorer 4WD 4dr	SOHC 4.0 V-6	5,740[d/e,f]
Explorer 4dr	5.0 V-8	5,820[c,f]
Explorer 4dr 4WD	5.0 V-8	5,620[c,f]
Explorer 4dr	5.0 V-8	6,820[d,f]
Explorer 4dr 4WD	5.0 V-8	6,620[d,f]
F-150, Manual Transmission, Conventional Towing:		
F-150	4.2 V-6	2,000[a]
F-150 4WD	4.2 V-6	2,600[b]
F-150	4.2 V-6	3,600[c]
F-150 4WD	4.2 V-6	3,200[c]
F-150	4.6 V-8	2,000[a]
F-150	4.6 V-8	2,900[b]
F-150	4.6 V-8	3,500[c]
F-150 4WD	4.6 V-8	3,100[c]
F-150 SuperCab	4.2 V-6	2,000[a]
F-150 SuperCab	4.2 V-6	3,300[c]
F-150 SuperCab	4.6 V-8	2,600[b]
F-150 SuperCab 4WD	4.6 V-8	2,300[b]
F-150 SuperCab	4.6 V-8	3,200[c]
F-150 SuperCab 4WD	4.6 V-8	2,900[c]
F-150, Automatic Transmission, Conventional Towing:		
F-150	4.2 V-6	4,800[b]
F-150	4.2 V-6	5,800[c]
F-150 4WD	4.2 V-6	5,400[c]
F-150	4.6 V-6	2,000[a]
F-150	4.6 V-8	6,200[b]
F-150 4WD	4.6 V-8	5,800[b]
F-150	4.6 V-8	7,200[c]
F-150 4WD	4.6 V-8	6,800[c]
F-150	5.4 V-8	7,500[b]
F-150 4WD	5.4 V-8	7,200[b]
F-150	5.4 V-8	8,500[c]
F-150 4WD	5.4 V-8	8,200[c]
F-150	5.4 V-8	8,800[d]
F-150 4WD	5.4 V-8	8,400[d]
F-150 SuperCab	4.2 V-6	5,500[c]
F-150 SuperCab	4.6 V-8	2,000[a]
F-150 SuperCab	4.6 V-8	5,900[b]
F-150 SuperCab 4WD	4.6 V-8	5,600[b]
F-150 SuperCab	4.6 V-8	6,900[c]
F-150 SuperCab 4WD	4.6 V-8	6,600[c]
F-150 SuperCab	5.4 V-8	7,300[b]
F-150 SuperCab 4WD	5.4 V-8	6,900[b]
F-150 SuperCab	5.4 V-8	8,300[c]
F-150 SuperCab 4WD	5.4 V-8	7,900[c]
F-150 SuperCab	5.4 V-8	8,700[d]
F-150 SuperCab 4WD	5.4 V-8	8,300[d]
F-150, Automatic Transmission, Fifth-Wheel Towing:		
F-150	4.2 V-6	5,800[c]
F-150 4WD	4.2 V-6	5,400[c]
F-150	4.6 V-8	7,200[c]
F-150 4WD	4.6 V-8	6,900[c]
F-150	5.4 V-8	8,600[c]
F-150 4WD	5.4 V-8	8,200[c]
F-150	5.4 V-8	8,800[d]
F-150 4WD	5.4 V-8	8,500[d]
F-150 SuperCab	4.2 V-6	5,500[c]
F-150 SuperCab	4.6 V-8	7,000[c]
F-150 SuperCab 4WD	4.6 V-8	6,600[c]
F-150 SuperCab	5.4 V-8	8,300[c]
F-150 SuperCab 4WD	5.4 V-8	8,000[c]
F-150 SuperCab	5.4 V-8	8,700[d]
F-150 SuperCab 4WD	5.4 V-8	8,300[d]
F-250/F-350 Super Duty, Manual Transmission, Conventional Towing:		
F-250	5.4 V-8	8,200[d]
F-250 4WD	5.4 V-8	7,700[d]
F-250	5.4 V-8	9,700[e]
F-250 4WD	5.4 V-8	9,200[e]
F-250 All Models	6.8 V-10	10,000[d,j]
F-250 All Models	7.3 TD	10,000[d]
F-350	5.4 V-8	8,100[d]
F-350	5.4 V-8	9,600[e]
F-350 DRW	5.4 V-8	7,800[d]
F-350 DRW	5.4 V-8	9,300[d]
F-350 4WD	5.4 V-8	7,700[d]
F-350 4WD	5.4 V-8	9,200[e]
F-350 4WD DRW	5.4 V-8	7,400[d]
F-350 4WD DRW	5.4 V-8	8,900[e]
F-350 All Models	6.8 V-10	10,000[d/j]
F-350 All Models	7.3 TD	10,000[d/e]
F-250 SuperCab	5.4 V-8	7,800[d]
F-250 SuperCab 4WD	5.4 V-8	7,400[d]
F-250 SuperCab	5.4 V-8	9,300[e]
F-250 SuperCab 4WD	5.4 V-8	8,900[e]
F-350 SuperCab	5.4 V-8	7,800[d]
F-350 SuperCab DRW	5.4 V-8	7,500[d]
F-350 SuperCab 4WD	5.4 V-8	7,400[d]
F-350 SuperCab	5.4 V-8	9,300[e]
F-350 SuperCab DRW	5.4 V-8	9,000[e]
F-350 SuperCab 4WD	5.4 V-8	8,900[e]
F-350 SuperCab 4WD DRW	5.4 V-8	8,700[e]
F-250 Crew Cab	5.4 V-8	7,500[d]
F-250 Crew Cab 4WD	5.4 V-8	7,100[d]
F-250 Crew Cab	5.4 V-8	9,000[e]
F-250 Crew Cab 4WD	5.4 V-8	8,600[e]
F-350 Crew Cab	5.4 V-8	7,500[d]
F-350 Crew Cab 4WD	5.4 V-8	7,100[d]
F-350 Crew Cab	5.4 V-8	9,000[e]
F-350 Crew Cab 4WD	5.4 V-8	8,600[e]
F-350 Crew Cab 4WD DRW	6.8 V-10	9,600[d]
F-350 All Models	6.8 V-10	10,000[d/j]
F-350 All Models	7.3 TD	10,000[d/e]

F-250/F-350 Super Duty, Automatic Transmission, Conventional Towing:		
F-250	5.4 V-8	8,100[d]
F-250 4WD	5.4 V-8	7,600[d]
F-250	5.4 V-8	9,600[e]
F-250 4WD	5.4 V-8	9,100[e]
F-250 All Models	6.8 V-10	10,000[d/j]
F-250 All Models	7.3 TD	10,000[d]
F-350	5.4 V-8	8,000[d]
F-350 DRW	5.4 V-8	7,800[d]
F-350	5.4 V-8	9,500[e]
F-350 DRW	5.4 V-8	9,300[e]
F-350 4WD	5.4 V-8	7,600[d]
F-350 4WD DRW	5.4 V-8	7,300[d]
F-350 4WD	5.4 V-8	9,100[e]
F-350 4WD DRW	5.4 V-8	8,800[e]
F-350 All Models	6.8 V-10	10,000[d/j]
F-350 All Models	7.3 TD	10,000[d/e]
F-250 SuperCab	5.4 V-8	7,700[d]
F-250 SuperCab 4WD	5.4 V-8	7,300[d]
F-250 SuperCab	5.4 V-8	9,200[e]
F-250 SuperCab 4WD	5.4 V-8	8,800[e]
F-350 SuperCab	5.4 V-8	7,700[d]
F-350 SuperCab DRW	5.4 V-8	7,500[d]
F-350 SuperCab 4WD	5.4 V-8	7,300[d]
F-350 SuperCab 4WD DRW	5.4 V-8	7,100[d]
F-350 SuperCab	5.4 V-8	9,200[e]
F-350 SuperCab DRW	5.4 V-8	9,000[e]
F-350 SuperCab 4WD	5.4 V-8	8,800[e]
F-350 SuperCab 4WD DRW	5.4 V-8	8,600[e]
F-250 Crew Cab	5.4 V-8	7,400[d]
F-250 Crew Cab 4WD	5.4 V-8	7,100[d]
F-250 Crew Cab	5.4 V-8	8,900[e]
F-250 Crew Cab 4WD	5.4 V-8	8,600[e]
F-250/F-350 Super Duty, Manual Transmission, Fifth-Wheel Towing:		
F-250	5.4 V-8	8,200[d]
F-250 4WD	5.4 V-8	7,700[d]
F-350	5.4 V-8	8,100[d]
F-350 DRW	5.4 V-8	7,800[d]
F-350 4WD	5.4 V-8	7,700[d]
F-350 4WD DRW	5.4 V-8	7,400[d]
F-250	5.4 V-8	9,700[e]
F-250 4WD	5.4 V-8	9,200[e]
F-350	5.4 V-8	9,600[e]
F-350 DRW	5.4 V-8	9,300[e]
F-350 4WD	5.4 V-8	9,200[e]
F-350 4WD DRW	5.4 V-8	8,900[e]
F-250	6.8 V-10	11,000[d]
F-250 4WD	6.8 V-10	10,500[d]
F-350	6.8 V-10	10,900[d]
F-350 DRW	6.8 V-10	10,600[d]
F-350 4WD	6.8 V-10	10,500[d]
F-350 4WD DRW	6.8 V-10	10,200[d]
F-250	6.8 V-10	14,500[j]
F-250 4WD	6.8 V-10	14,000[j]
F-350	6.8 V-10	14,400[j]
F-350 DRW	6.8 V-10	14,100[j]
F-350 4WD	6.8 V-10	14,000[j]
F-350 4WD DRW	6.8 V-10	13,700[j]
F-250	7.3 TD	14,000[d]
F-250 4WD	7.3 TD	13,500[d]
F-350	7.3 TD	13,900[d]
F-350 DRW	7.3 TD	13,600[d/e]
F-350 4WD	7.3 TD	13,500[d]
F-350 4WD DRW	7.3 TD	13,100[d/e]
F-250 SuperCab	5.4 V-8	7,800[d]
F-250 SuperCab 4WD	5.4 V-8	7,400[d]
F-250 Crew Cab	5.4 V-8	7,500[d]
F-250 Crew Cab 4WD	5.4 V-8	7,100[d]
F-250 SuperCab	5.4 V-8	9,300[d]
F-250 SuperCab 4WD	5.4 V-8	8,900[e]
F-250 Crew Cab	5.4 V-8	9,000[e]
F-250 Crew Cab 4WD	5.4 V-8	8,600[e]
F-250 SuperCab	6.8 V-10	10,600[d]
F-250 SuperCab 4WD	6.8 V-10	10,200[d]
F-250 Crew Cab	6.8 V-10	10,300[d]
F-250 Crew Cab 4WD	6.8 V-10	10,000[d]
F-250 SuperCab	7.3 TD	13,600[d]
F-250 SuperCab 4WD	7.3 TD	13,200[d]
F-250 Crew Cab	7.3 TD	13,300[d]
F-250 Crew Cab 4WD	7.3 TD	12,900[d]
F-350 SuperCab	5.4 V-8	7,700[d]
F-350 SuperCab DRW	5.4 V-8	7,500[d]
F-350 SuperCab 4WD	5.4 V-8	7,400[d]
F-350 SuperCab 4WD DRW	5.4 V-8	7,200[d]
F-350 Crew Cab	5.4 V-8	7,500[d]
F-350 Crew Cab 4WD	5.4 V-8	7,100[d]
F-350 SuperCab	5.4 V-8	9,300[e]
F-350 SuperCab DRW	5.4 V-8	9,000[e]
F-350 SuperCab 4WD	5.4 V-8	8,900[e]
F-350 SuperCab 4WD DRW	5.4 V-8	8,700[e]
F-350 Crew Cab	5.4 V-8	8,900[e]
F-350 Crew Cab 4WD	5.4 V-8	8,600[e]
F-350 SuperCab	6.8 V-10	10,600[d]
F-350 SuperCab DRW	6.8 V-10	10,300[d]
F-350 SuperCab 4WD	6.8 V-10	10,200[d]
F-350 SuperCab 4WD DRW	6.8 V-10	10,000[d]
F-350 Crew Cab	6.8 V-10	10,300[d]
F-350 Crew Cab DRW	6.8 V-10	10,000[d]
F-350 Crew Cab 4WD	6.8 V-10	10,000[d]
F-350 Crew Cab 4WD DRW	6.8 V-10	9,600[d]
F-350 SuperCab	6.8 V-10	14,100[j]
F-350 SuperCab DRW	6.8 V-10	13,800[j]
F-350 SuperCab 4WD	6.8 V-10	13,700[j]
F-350 SuperCab 4WD DRW	6.8 V-10	13,500[j]
F-350 Crew Cab	6.8 V-10	13,800[j]
F-350 Crew Cab DRW	6.8 V-10	13,500[j]
F-350 Crew Cab 4WD	6.8 V-10	13,500[j]
F-350 Crew Cab 4WD DRW	6.8 V-10	13,100[j]
F-350 SuperCab	7.3 TD	13,600[d]
F-350 SuperCab DRW	7.3 TD	13,300[d/e]
F-350 SuperCab 4WD	7.3 TD	13,200[d]
F-350 SuperCab 4WD DRW	7.3 TD	12,900[d/e]
F-350 Crew Cab	7.3 TD	13,300[d]
F-350 Crew Cab DRW	7.3 TD	13,000[d/e]
F-350 Crew Cab 4WD	7.3 TD	13,000[d]
F-350 Crew Cab 4WD DRW	7.3 TD	12,600[d/e]
F-250/F-350 Super Duty, Automatic Transmission, Fifth-Wheel Towing:		
F-250	5.4 V-8	8,100[d]
F-250 4WD	5.4 V-8	7,600[d]
F-350	5.4 V-8	8,000[d]
F-350 DRW	5.4 V-8	7,800[d]
F-350 4WD	5.4 V-8	7,600[d]
F-350 4WD DRW	5.4 V-8	7,300[d]
F-250	5.4 V-8	9,600[e]
F-250 4WD	5.4 V-8	9,100[e]
F-350	5.4 V-8	9,500[e]
F-350 DRW	5.4 V-8	9,300[e]
F-350 4WD	5.4 V-8	9,100[e]
F-350 4WD DRW	5.4 V-8	8,800[e]
F-250	6.8 V-10	11,500[d]
F-250 4WD	6.8 V-10	11,000[d]
F-350	6.8 V-10	11,400[d]
F-350 DRW	6.8 V-10	11,100[d]
F-350 4WD	6.8 V-10	11,000[d]
F-250 4WD DRW	6.8 V-10	10,600[d]
F-250	6.8 V-10	14,500[j]
F-250 4WD	6.8 V-10	14,000[j]
F-350	6.8 V-10	14,400[j]
F-350 DRW	6.8 V-10	14,100[j]
F-350 4WD	6.8 V-10	14,000[j]
F-250 4WD DRW	6.8 V-10	13,600[j]
F-250	7.3 TD	14,000[d]
F-250 4WD	7.3 TD	13,500[d]
F-350	7.3 TD	13,900[d]
F-350 DRW	7.3 TD	13,600[d/e]
F-350 4WD	7.3 TD	13,500[d]
F-250 SuperCab	5.4 V-8	7,700[d]
F-250 SuperCab 4WD	5.4 V-8	7,300[d]
F-250 Crew Cab	5.4 V-8	7,400[d]
F-250 Crew Cab 4WD	5.4 V-8	7,100[d]
F-250 SuperCab	5.4 V-8	9,200[e]
F-250 SuperCab 4WD	5.4 V-8	8,800[e]
F-250 Crew Cab	5.4 V-8	8,900[e]
F-250 Crew Cab 4WD	5.4 V-8	8,600[e]
F-250 SuperCab	6.8 V-10	11,100[d]
F-250 SuperCab 4WD	6.8 V-10	10,700[d]
F-250 Crew Cab	6.8 V-10	10,800[d]
F-250 Crew Cab 4WD	6.8 V-10	10,400[d]
F-250 SuperCab	6.8 V-10	14,100[j]
F-250 SuperCab 4WD	6.8 V-10	13,700[j]
F-250 Crew Cab	6.8 V-10	13,800[j]
F-250 Crew Cab 4WD	6.8 V-10	13,400[j]
F-250 SuperCab	7.3 TD	13,700[d]
F-250 Crew Cab 4WD	7.3 TD	13,200[d]
F-250 Crew Cab	7.3 TD	13,400[d]
F-250 Crew Cab 4WD	7.3 TD	13,000[d]
F-350 SuperCab	5.4 V-8	7,700[d]
F-350 SuperCab DRW	5.4 V-8	7,500[d]
F-350 SuperCab 4WD	5.4 V-8	7,300[d]
F-350 SuperCab 4WD DRW	5.4 V-8	7,100[d]
F-350 Crew Cab	5.4 V-8	7,400[d]
F-350 Crew Cab 4WD	5.4 V-8	7,100[d]
F-350 SuperCab	5.4 V-8	9,200[e]
F-350 SuperCab DRW	5.4 V-8	9,000[e]
F-350 SuperCab 4WD	5.4 V-8	8,800[e]
F-350 SuperCab 4WD DRW	5.4 V-8	8,600[e]
F-350 Crew Cab	5.4 V-8	8,900[e]
F-350 Crew Cab 4WD	5.4 V-8	8,600[e]
F-350 SuperCab	6.8 V-10	11,100[d]
F-350 SuperCab DRW	6.8 V-10	10,800[d]
F-350 SuperCab 4WD	6.8 V-10	10,700[d]
F-350 SuperCab 4WD DRW	6.8 V-10	10,400[d]
F-350 Crew Cab	6.8 V-10	10,800[d]
F-350 Crew Cab DRW	6.8 V-10	10,500[d]
F-350 Crew Cab 4WD	6.8 V-10	10,400[d]
F-350 Crew Cab 4WD DRW	6.8 V-10	10,000[a,k]
F-350 SuperCab	6.8 V-10	14,100[j]
F-350 SuperCab DRW	6.8 V-10	13,800[j]
F-350 SuperCab 4WD	6.8 V-10	13,700[j]
F-350 SuperCab 4WD DRW	6.8 V-10	13,400[j]
F-350 Crew Cab	6.8 V-10	13,800[j]
F-350 Crew Cab DRW	6.8 V-10	13,500[j]
F-350 Crew Cab 4WD	6.8 V-10	13,400[j]
F-350 Crew Cab 4WD DRW	6.8 V-10	13,000[j]
F-350 SuperCab	7.3 TD	13,600[d]
F-350 SuperCab DRW	7.3 TD	13,400[d/e]
F-350 SuperCab 4WD	7.3 TD	13,300[d]
F-350 SuperCab 4WD DRW	7.3 TD	13,000[d/e]
F-350 Crew Cab	7.3 TD	13,300[d]
F-350 Crew Cab DRW	7.3 TD	13,000[d/e]
F-350 Crew Cab 4WD	7.3 TD	13,000[d]
F-350 Crew Cab 4WD DRW	7.3 TD	12,600[d/e]
F-450/F-550 Super Duty, Manual Transmission, Fifth-Wheel Towing:		
F-450	6.8 V-10	14,700[k,l]
F-450 4WD	6.8 V-10	14,400[k,l]
F-450	7.3 TD	18,200[k]
F-450 4WD	7.3 TD	17,900[k]
F-550	7.3 TD	18,100[k]
F-550 4WD	7.3 TD	17,800[k]
F-450 Crew Cab	6.8 V-10	14,200[k,l]
F-450 Crew Cab 4WD	6.8 V-10	13,800[k,l]
F-450 Crew Cab	7.3 TD	17,600[k]
F-450 Crew Cab 4WD	7.3 TD	17,300[k]
F-550 Crew Cab	7.3 TD	17,500[k]
F-550 Crew Cab 4WD	7.3 TD	17,200[k]
F-450/F-550 Super Duty, Automatic Transmission, Fifth-Wheel Towing:		
F-450	6.8 V-10	16,700[k]
F-450 4WD	6.8 V-10	16,400[k]
F-450	6.8 V-10	18,700[l]
F-450 4WD	6.8 V-10	18,400[l]
F-550 4WD	6.8 V-10	16,600[k]
F-550 4WD	6.8 V-10	16,300[k]
F-550	6.8 V-10	18,600[l]
F-550 4WD	6.8 V-10	18,300[l]
F-450	7.3 TD	18,200[k]
F-450 4WD	7.3 TD	17,900[k]
F-550	7.3 TD	18,100[k]
F-550 4WD	7.3 TD	17,800[k]
F-450 Crew Cab	6.8 V-10	16,100[k]
F-450 Crew Cab 4WD	6.8 V-10	15,800[k]
F-550 Crew Cab	6.8 V-10	16,000[k]
F-550 Crew Cab 4WD	6.8 V-10	15,700[k]
F-450 Crew Cab	6.8 V-10	18,100[l]
F-450 Crew Cab 4WD	6.8 V-10	17,800[l]
F-550 Crew Cab	6.8 V-10	18,600[l]
F-550 Crew Cab 4WD	6.8 V-10	17,700[l]
F-450 Crew Cab	7.3 TD	17,600[k]
F-450 Crew Cab 4WD	7.3 TD	17,300[k]
F-550 Crew Cab	7.3 TD	17,600[k]
F-550 Crew Cab 4WD	7.3 TD	17,200[k]
Ranger, Automatic Transmission:		
Ranger	2.5 I-4	2,180[e]
Ranger	3.0 V-6	4,120[e]
Ranger 4WD	3.0 V-6	3,860[d]
Ranger 4WD	3.0 V-6	4,360[e]
Ranger SuperCab 4WD	3.0 V-6	3,660[d]
Ranger SuperCab 4WD	3.0 V-6	4,160[e]
Ranger	4.0 V-6	6,060[c]
Ranger SuperCab	4.0 V-6	5,860[c]
Ranger 4WD	4.0 V-6	5,800[d/e]
Ranger SuperCab 4WD	4.0 V-6	5,620[d/e]
Ranger, Manual Transmission:		
Ranger	3.0 V-6	2,660[d]
Ranger 4WD	3.0 V-6	2,400[d/e]
Ranger SuperCab	3.0 V-6	2,460[d/e]
Ranger SuperCab 4WD	3.0 V-6	2,200[d/e]
Ranger 4WD	4.0 V-6	3,340[d/e]
Ranger SuperCab 4WD	4.0 V-6	3,160[d/e]
Ranger	4.0 V-6	3,600[c]
Ranger SuperCab	4.0 V-6	3,400[c]
Windstar:		
Windstar	3.0 V-6	2,000[e]
Windstar	3.8 V-6	3,500[a]

TD = Turbodiesel

[a]Requires 3.08:1 axle ratio.
[b]Requires 3.31:1 axle ratio.
[c]Requires 3.55:1 axle ratio.
[d]Requires 3.73:1 axle ratio.
[e]Requires 3.98/4.09/4.10:1 axle ratio.
[f]Must be equipped with heavy-duty towing package.
[g]Requires 16-inch wheel option.
[h]Requires 17-inch wheel option.
[i]Requires 3.27:1 axle ratio.
[j]Requires 4.30:1 axle ratio.
[k]Requires 4.88:1 axle ratio.
[l]Requires 5.38:1 axle ratio.

HONDA

Vehicle	Engine	Tow Limit (lbs.)
Odyssey	V-6 24-valve	3,500[a,b]
Passport	3.2 V-6	4,500
Acura RL	3.5	2,000

[a]With transmission fluid cooler and two occupants. Deduct 150 pounds per passenger up to seven passengers.
[b]Without transmission cooler: 2,000 pounds maximum with two occupants.

HYUNDAI

Vehicle	Engine	Tow Limit (lbs.)
Sonata	V-6	2,000[a,b]

[a]Manual or automatic transmission.
[b]Trailer must have brakes (without brakes = 1,000 pounds).

INFINITI

Vehicle	Engine	Tow Limit (lbs.)
QX4	3.3 V-6	5,000

ISUZU

Vehicle	Engine	Tow Limit (lbs.)
Hombre/Rodeo/Amigo	2.2/2.6 I-4	2,000
Amigo	3.2 V-6	4,500
Rodeo	3.2 V-6	4,500
Trooper	3.2 V-6	5,000
Hombre	4.3 V-6	5,500

JAGUAR

Vehicle	Engine	Tow Limit (lbs.)
S-type	4.0 I-6	3,307

JEEP

Vehicle	Engine	Tow Limit (lbs.)
Cherokee/Wrangler	2.5 I-4	2,000[a]
Cherokee/Grand Cherokee	4.0 I-6	5,000[b,c,d]
Wrangler	4.0 I-6	2,000[f]
Grand Cherokee	4.7 V-8	6,500[b,c,d,e]
Grand Cherokee Limited (4WD)	4.7 V-8	5,000[b]

NOTE: Trailer brakes required on all trailers weighing more than 1,000 pounds.

[a]Wrangler rating is 1,000 pounds with automatic transmission.
[b]Requires weight-distributing hitch with a maximum hitch weight of 750 pounds.
[c]Requires trailer-towing package.
[d]Requires automatic transmission.
[e]4WD rated 200 pounds lower.
[f]Maximum hitch weight of 300 pounds.

KIA

Vehicle	Engine	Tow Limit (lbs.)
Sportage All Models	2.0 I-4	2,000

LAND ROVER

Vehicle	Engine	Tow Limit (lbs.)
Discovery, Series II	All	5,500[a,b]
Range Rover	All	6,500[a,b]

[a]Maximum trailer weight without brakes is 1,650 pounds.
[b]Off-road maximum is 2,200 pounds.

LEXUS

Vehicle	Engine	Tow Limit (lbs.)
LS/ES Models	All	2,000
LX 470	4.7 V-8	6,500
RX 300	3.0 V-6	3,500

LINCOLN

Vehicle	Engine	Tow Limit (lbs.)
Town Car & LS	4.6 V-8	2,000
Navigator	5.4 V-8	8,900[a,b]

[a]Requires optional Class III Trailer Tow Package with load-equalizing hitch.
[b]4WD tow rating is 8,100 pounds.

MAZDA

Vehicle	Engine	Tow Limit (lbs.)
B2500	2.5 I-4	2,240[a,e]
B3000	3.0 V-6	4,000[a,d,e]
B3000 4WD	3.0 V-6	4,360[a,d,e]
B4000	4.0 V-6	6,000[a,c,d,e]
B4000 4WD	4.0 V-6	5,700[a,c,d]
MPV	3.0 V-6	4,300[b]
MPV AWD	3.0 V-6	4,000[b]

[a]Requires automatic transmission; rating lower with manual transmission.
[b]Requires trailer-towing package.
[c]Requires special axle ratio and trailer-towing package.
[d]Requires load-equalizing hitch for more than 2,000 pounds.
[e]Cab Plus rating lower.

MERCEDES-BENZ

Vehicle	Engine	Tow Limit (lbs.)
ML 320	3.2 V-6	5,000

MERCURY

Vehicle	Engine	Tow Limit (lbs.)
Grand Marquis	4.6 V-8	2,000
Mountaineer	4.0 V-6	4,900[a,b,c]
Mountaineer	4.0 V-6	5,900[a,b,d]
Mountaineer	5.0 V-8	5,760[a,b,c]
Mountaineer	5.0 V-8	6,760[a,b,d]
Mountaineer AWD	4.0 V-6	4,700[a,b,c]
Mountaineer AWD	4.0 V-6	5,700[a,b,d]
Mountaineer AWD	5.0 V-8	5,560[a,b,c]
Mountaineer AWD	5.0 V-8	6,560[a,b,d]
Villager	3.0 V-6	3,500[a]

[a]Requires load-equalizing hitch.
[b]Requires optional towing package.
[c]Requires 3.55:1 gear ratio.
[d]Requires 3.73:1 gear ratio.

MITSUBISHI

Vehicle	Engine	Tow Limit (lbs.)
Montero	3.5 V-6	5,000[a]
Montero Sport ES	2.4 I-4	2,300[a]
Montero Sport LS, XLS	3.0 V-6	5,000[a]

[a]Tow rating with trailer brakes; 1,500 pounds maximum rating without.

NISSAN

Vehicle	Engine	Tow Limit (lbs.)
Pathfinder/Frontier	3.3 V-6	5,000[a]
Xterra/Frontier	2.4 I-4	3,500[b,c]
Xterra	3.3 V-6	5,000[d]
Quest	3.0 V-6	3,500[b]

[a]Rating is 3,500 pounds with manual transmission.
[b]Requires manual transmission.
[c]Rating is 2,000 pounds with automatic transmission.
[d]Automatic transmission required.

OLDSMOBILE

Vehicle	Engine	Tow Limit (lbs.)
Bravada	4.3 V-6	5,000[a]
Silhouette	3.4 V-6	3,500[a,b]

[a]Frame-mounted hitch required.
[b]Requires towing package.

PLYMOUTH

Vehicle	Engine	Tow Limit (lbs.)
Voyager	3.0 V-6	2,000[a,b]
Voyager	3.8 V-6	3,500[a,b]

NOTE: Trailers more than 1,000 pounds must have brakes.

[a]Four-speed automatic transmission required.
[b]Requires heavy-duty towing package with frame-mounted hitch.

PONTIAC

Vehicle	Engine	Tow Limit (lbs.)
Montana	3.4 V-6	3,500[a]

[a]Requires towing package.

SAAB

Vehicle	Engine	Tow Limit (lbs.)
All	All	2,000[a]

[a]Maximum trailer weight without brakes is 1,000 pounds.

SUBARU

Vehicle	Engine	Tow Limit (lbs.)
Legacy/Outback/Forester	2.5 SOHC I-4	2,000[a]

[a]Trailer brakes required. Maximum hitch weight 200 pounds.

TOYOTA

Vehicle	Engine	Tow Limit (lbs.)
4Runner	2.7 I-4	3,500[a]
4Runner	3.4 V-6	5,000[a]
Camry/Avalon	All	2,000[a]
Land Cruiser	4.7 V-8	6,500[b]
Sienna	3.0 V-6	3,500[a,c]
Tacoma	All I-4	3,500[a]
Tacoma	3.4 V-6	5,000[a]
Tundra	4.7 V-8	7,200[c]
Tundra	3.4 V-6 M	5,250[c,d]
Tundra	3.4 V-6 A	5,200[c,d]

M = Manual transmission A = Automatic transmission

[a]Maximum hitch weight 10 percent of tow limit.
[b]Not to exceed 12,000 pounds gcwr with appropriate hitch.
[c]With optional towing package.
[d]Tow rating of 4WD is 300 pounds lower.

VOLVO

Vehicle	Engine	Tow Limit (lbs.)
All, except S40 & V40	All	3,300[a]
S40 & V40	All	2,000[a]

[a]Volvo hitch is recommended. When towing trailers more than 1,540 pounds, brakes are required.