

# 2002 TOW RATINGS

*Compiled by Chris Hemer*

**F**or 2002 there are even more new models, not to mention a multitude of new technologies sure to find favor with RVers. To help simplify things, we have combined some columns, such as conventional/fifth-wheel tow ratings and manual/automatic tow ratings. This not only helps shorten the guide, it makes it easier for you to make direct comparisons between truck/trailer setups with respect to their maximum tow capacities. In addition, you'll note that we have excluded passenger car tow ratings from this year's list (since precious few are rated to tow more than 2,000 pounds), as well as some less-popular vehicle models. These vehicles will be included in the complete TL tow rating booklet, available separately. And as usual, vehicles capable of towing under 2,000 pounds will be excluded from both guides.

Every effort has been made to ensure the accuracy of all ratings, but because our information is often preliminary at the time of publication, some numbers may have changed by the time you visit your dealer's showroom. When in doubt, consult the manufacturer's towing guide (available at your dealership) or the vehicle owner's manual to be certain.

## ACURA

| Vehicle   | Engine  | Tow Limit (lbs) |
|-----------|---------|-----------------|
| Acura RL  | 3.5 V-6 | 2,000           |
| Acura MDX | 3.5 V-6 | 4,500a,b        |

a=requires automatic transmission and power steering coolers when towing more than 2,000 lbs; b=maximum rated capacity of 4500 lbs is for towing boats, 3,500 for towing other trailers.

## BMW

| Vehicle      | Engine  | Tow Limit (lbs) |
|--------------|---------|-----------------|
| BMW X5 4.6is | 4.6 V8  | 6,000 a,b,d     |
| BMW X5       | 4.4 V8  | 6,000a,b,d      |
| BMW X5       | 3.0 I-6 | 6,000a,b,c      |
| BMW X5       | 3.0 I-6 | 5,000a,b,d      |

a=Maximum towing weight for trailers without brakes is 1,650 lbs; b=Maximum towing weight for trailers with brakes off-road, 3,300 lbs; c=With manual transmission; d=With automatic transmission

## BUICK

| Vehicle    | Engine  | Tow Limit |
|------------|---------|-----------|
| Rendezvous | 3.4 V-6 | 3,500a    |

a=requires towing package.

## CADILLAC

| Vehicle      | Engine  | Tow Limit (lbs) |
|--------------|---------|-----------------|
| Escalade AWD | 6.0 V-8 | 8,200           |
| Escalade 2WD | 5.3 V-8 | 7,400           |
| Escalade EXT | 6.0 V-8 | 7,900           |

a=Requires trailer-towing package.

## CHEVROLET/GMC

### Astro/Safari and Venture Minivans

| Vehicle | Engine  | Tow Limit (lbs) |
|---------|---------|-----------------|
| RWD CV  | 4.3 V-6 | 5,300a          |
| RWD CV  | 4.3 V-6 | 5,800b          |
| RWD PV  | 4.3 V-6 | 4,900a          |
| RWD PV  | 4.3 V-6 | 5,400b          |
| AWD CV  | 4.3 V-6 | 5,100a          |
| AWD CV  | 4.3 V-6 | 5,600b          |
| AWD PV  | 4.3 V-6 | 4,700a          |
| AWD PV  | 4.3 V-6 | 5,200b          |
| Venture | 3.4 V-6 | 3,500d          |

### Express/Savana

| Vehicle     | Engine  | Tow Limit (lbs) |
|-------------|---------|-----------------|
| G1500 CV    | 4.3 V-6 | 4,700a          |
| G1500 CV    | 4.3 V-6 | 5,200b          |
| G1500 CV    | 5.0 V-8 | 5,600a          |
| G1500 CV    | 5.7 V-8 | 6,100a          |
| G1500 PV    | 4.3 V-6 | 4,200a          |
| G1500 PV    | 4.3 V-6 | 4,700b          |
| G1500 PV    | 5.0 V-8 | 5,100a          |
| G1500 PV    | 5.7 V-8 | 5,600a          |
| G1500 PV    | 5.7 V-8 | 6,600b          |
| G2500 CV    | 4.3 V-6 | 4,500a          |
| G2500 CV    | 5.0 V-8 | 5,400a          |
| G2500 CV    | 5.7 V-8 | 5,900a          |
| G2500 CV HD | 4.3 V-6 | 5,200c          |
| G2500 CV HD | 5.7 V-8 | 6,600b          |

| Vehicle         | Engine  | Tow Limit (lbs) |
|-----------------|---------|-----------------|
| G2500 CV HD     | 5.7 V-8 | 8,100c          |
| G2500 CV HD     | 6.5 TD  | 8,600b/c        |
| G2500 LWB CV    | 4.3 V-6 | 4,300a          |
| G2500 LWB CV    | 5.0 V-8 | 5,200a          |
| G2500 LWB CV    | 5.7 V-8 | 5,700a          |
| G2500 LWB CV HD | 4.3 V-6 | 5,000c          |
| G2500 LWB CV HD | 5.7 V-8 | 6,400b          |
| G2500 LWB CV HD | 5.7 V-8 | 7,900c          |
| G2500 LWB CV HD | 6.5 TD  | 8,400b/c        |
| G2500 PV        | 5.7 V-8 | 6,000b          |
| G2500 PV        | 5.7 V-8 | 7,500c          |
| G2500 PV        | 6.5 TD  | 8,000b/c        |
| G2500 LWB PV    | 5.7 V-8 | 5,800b          |
| G2500 LWB PV    | 5.7 V-8 | 7,300c          |
| G3500 CV        | 5.7 V-8 | 6,400b          |
| G3500 CV        | 5.7 V-8 | 7,900c          |
| G3500 CV        | 8.1 V-8 | 9,100b          |
| G3500 CV        | 8.1 V-8 | 10,000c         |
| G3500 CV        | 6.5 TD  | 8,600b/c        |
| G3500 LWB CV    | 5.7 V-8 | 6,200b          |
| G3500 LWB CV    | 5.7 V-8 | 7,700c          |
| G3500 LWB CV    | 8.1 V-8 | 8,900b          |
| G3500 LWB CV    | 8.1 V-8 | 10,000c         |
| G3500 LWB CV    | 6.5 TD  | 8,400b/c        |
| G3500 PV        | 5.7 V-8 | 5,800b          |
| G3500 PV        | 5.7 V-8 | 7,300c          |
| G3500 PV        | 8.1 V-8 | 8,500b          |
| G3500 PV        | 8.1 V-8 | 10,000c         |
| G3500 PV        | 6.5 TD  | 8,000b/c        |
| G3500 LWB PV    | 5.7 V-8 | 5,600b          |
| G3500 LWB PV    | 5.7 V-8 | 7,100c          |
| G3500 LWB PV    | 8.1 V-8 | 8,300b          |
| G3500 LWB PV    | 8.1 V-8 | 10,000c         |
| G3500 LWB PV    | 6.5 TD  | 7,800b/c        |

LWB=Long Wheelbase; PV=Passenger Van; CV=Cargo Van; TD=Turbo Diesel; a=3.42:1 axle ratio; b=3.73:1 axle ratio; c=4:10:1 axle ratio; d= requires heavy duty tow package.

### Blazer

| Vehicle                | Engine  | Tow Limit (lbs) |
|------------------------|---------|-----------------|
| 2dr. 2WD               | 4.3 V-6 | 4,700a,c        |
| 2dr. 2WD               | 4.3 V-6 | 5,700a,d        |
| 2dr. 2WD               | 4.3 V-6 | 4,200b,d        |
| Blazer Xtreme 2dr. 2WD | 4.3 V-6 | 2,000a,b,d      |
| 4dr. 2WD               | 4.3 V-6 | 4,500a,c        |
| 4dr. 2WD               | 4.3 V-6 | 5,500a,d        |
| 2dr. 4WD               | 4.3 V-6 | 4,400a,c        |
| 2dr. 4WD               | 4.3 V-6 | 5,400a,d/e      |
| 2dr. 4WD               | 4.3 V-6 | 3,900b,d        |
| Blazer ZR2             | 4.3 V-6 | 4,100b,e        |
| Blazer ZR2             | 4.3 V-6 | 4,600a,e        |
| 4dr. 4WD               | 4.3 V-6 | 4,200a,c        |
| 4dr. 4WD               | 4.3 V-6 | 5,200a,d/e      |
| 4dr. 4WD               | 4.3 V-6 | 3,600b,d        |

### S-10/Sonoma

| Vehicle     | Engine  | Tow Limit (lbs) |
|-------------|---------|-----------------|
| Regular Cab | 2.2 I-4 | 3,200a,f        |
| Regular Cab | 4.3 V-6 | 4,000a,c        |
| Regular Cab | 4.3 V-6 | 5,000a,c        |

| Vehicle          | Engine  | Tow Limit (lbs) |
|------------------|---------|-----------------|
| Regular Cab      | 4.3 V-6 | 6,000a,d        |
| Extended Cab     | 2.2 I-4 | 2,000b,f        |
| Extended Cab     | 2.2 I-4 | 3,000a,f        |
| Extended Cab     | 4.3 V-6 | 3,800b,c        |
| Extended Cab     | 4.3 V-6 | 4,800a,c        |
| Extended Cab     | 4.3 V-6 | 5,800a,d        |
| Long Bed*        | 2.2 I-4 | 2,200b,f        |
| Long Bed*        | 2.2 I-4 | 3,100a,f        |
| Long Bed*        | 4.3 V-6 | 3,900b,c        |
| Long Bed*        | 4.3 V-6 | 4,900a,c        |
| Long Bed*        | 4.3 V-6 | 5,900a,d        |
| Extended cab 4WD | 4.3 V-6 | 4,000b,d        |
| Extended cab 4WD | 4.3 V-6 | 5,500a,d/e      |
| S-10 ZR2         | 4.3 V-6 | 4,200b,e        |
| S-10 ZR2         | 4.3 V-6 | 4,700a,e        |
| Crew Cab 4WD     | 4.3 V-6 | 5,200a,d/e      |

a=automatic transmission; b=manual transmission; c=3.08:1 rear axle ratio; d=3.42:1 rear axle ratio; e=3.73:1 rear axle ratio; f=4.10:1 rear axle ratio; \*late availability

### Chevy Avalanche 1500/2500

| Vehicle     | Engine  | Tow Limit (lbs) |
|-------------|---------|-----------------|
| 1500 CC     | 5.3 V-8 | 7,300d          |
| 1500 CC     | 5.3 V-8 | 8,300e          |
| 2500 CC     | 8.1 V-8 | 10,400d         |
| 2500 CC     | 8.1 V-8 | 12,000e         |
| 1500 CC 4WD | 5.3 V-8 | 7,100d          |
| 1500 CC 4WD | 5.3 V-8 | 8,100e          |
| 2500 CC 4WD | 8.1 V-8 | 10,100d         |
| 2500 CC 4WD | 8.1 V-8 | 12,000e         |

### Sierra/Silverado Light Duty, Automatic Transmission, Conventional/Fifth-Wheel Towing (Automatic or Manual with 6.0 V-8)

| Vehicle    | Engine  | Tow Limit (lbs)<br>Conv/5th-Wheel |
|------------|---------|-----------------------------------|
| 1500       | 4.3 V-6 | 4,600a/NA                         |
| 1500       | 4.3 V-6 | 5,200c/NA                         |
| 1500       | 4.8 V-8 | 6,600c/6,500c                     |
| 1500       | 4.8 V-8 | 7,600d                            |
| 1500       | 5.3 V-8 | 7,600c                            |
| 1500       | 5.3 V-8 | 8,600d                            |
| 1500 EC    | 4.3 V-6 | 4,700c/NA                         |
| 1500 EC    | 4.3 V-6 | 5,200d/NA                         |
| 1500 EC    | 4.8 V-8 | 6,100c                            |
| 1500 EC    | 4.8 V-8 | 7,300d                            |
| 1500 EC    | 5.3 V-8 | 7,300c                            |
| 1500 EC    | 5.3 V-8 | 8,300d                            |
| CC         | 6.0 V-8 | 8,300d                            |
| CC         | 6.0 V-8 | 10,300e                           |
| 1500 LB    | 4.3 V-6 | 4,500a/NA                         |
| 1500 LB    | 4.3 V-6 | 5,100c/NA                         |
| 1500 LB    | 4.8 V-8 | 6,500c/6,400c                     |
| 1500 LB    | 4.8 V-8 | 7,500d                            |
| 1500 LB    | 5.3 V-8 | 7,500c                            |
| 1500 LB    | 5.3 V-8 | 8,500d                            |
| 1500 LB EC | 4.8 V-8 | 6,100c                            |
| 1500 LB EC | 4.8 V-8 | 7,100d                            |
| 1500 LB EC | 5.3 V-8 | 7,100c                            |
| 1500 LB EC | 5.3 V-8 | 8,100d                            |

| Vehicle        | Engine  | Tow Limit (lbs)<br>Conv/5th-Wheel |
|----------------|---------|-----------------------------------|
| 2500 LB        | 6.0 V-8 | 8,800d                            |
| 2500 LB        | 6.0 V-8 | 10,800e                           |
| Sierra Denali  | 6.0 V-8 | 10,000                            |
| 1500 4WD       | 4.3 V-6 | 4,800c/NA                         |
| 1500 4WD       | 4.3 V-6 | 5,400d/NA                         |
| 1500 4WD       | 4.8 V-8 | 7,300d/7,200d                     |
| 1500 4WD       | 4.8 V-8 | 8,300e/8,200e                     |
| 1500 4WD       | 5.3 V-8 | 8,300d                            |
| 1500 4WD       | 5.3 V-8 | 9,300e                            |
| 1500 4WD EC    | 4.8 V-8 | 6,800d                            |
| 1500 4WD EC    | 4.8 V-8 | 8000e                             |
| 1500 4WD EC    | 5.3 V-8 | 8,000d                            |
| 1500 4WD EC    | 5.3 V-8 | 9,000e                            |
| 1500 4WD CC    | 6.0 V-8 | 8,000d                            |
| 1500 4WD CC    | 6.0 V-8 | 10,000e                           |
| 1500 4WD LB    | 4.3 V-6 | 4,700c/NA                         |
| 1500 4WD LB    | 4.3 V-6 | 5,200d/NA                         |
| 1500 4WD LB    | 4.8 V-8 | 7,100d                            |
| 1500 4WD LB    | 4.8 V-8 | 8,100e                            |
| 1500 4WD LB    | 5.3 V-8 | 8,100d                            |
| 1500 4WD LB    | 5.3 V-8 | 9,100e                            |
| 1500 4WD LB EC | 4.8 V-8 | 6,700d                            |
| 1500 4WD LB EC | 4.8 V-8 | 7,700e                            |
| 1500 4WD LB EC | 5.3 V-8 | 7,700d                            |
| 1500 4WD LB EC | 5.3 V-8 | 8,700e                            |
| 2500 4WD EC    | 6.0 V-8 | 8,300d                            |
| 2500 4WD EC    | 6.0 V-8 | 10,300e                           |

### Sierra/Silverado Light Duty, Manual Transmission, Conventional Towing

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| 1500           | 4.3 V-6 | 3,600a          |
| 1500           | 4.3 V-6 | 4,200c          |
| 1500           | 4.8 V-8 | 4,600c          |
| 1500           | 4.8 V-8 | 5,600d          |
| 1500 EC        | 4.3 V-6 | 3,700c          |
| 1500 EC        | 4.8 V-8 | 4,200c          |
| 1500 EC        | 4.8 V-8 | 5,300d          |
| 1500 LB        | 4.3 V-6 | 3,600a          |
| 1500 LB        | 4.3 V-6 | 4,100c          |
| 1500 LB        | 4.8 V-8 | 4,500c          |
| 1500 LB        | 4.8 V-8 | 5,500d          |
| 1500 LB EC     | 4.8 V-8 | 4,100c          |
| 1500 LB EC     | 4.8 V-8 | 5,100d          |
| 2500 LB        | 6.0 V-8 | 8,800d          |
| 2500 LB        | 6.0 V-8 | 10,800e         |
| 1500 4WD       | 4.3 V-6 | 3,800c          |
| 1500 4WD       | 4.3 V-6 | 4,400d          |
| 1500 4WD       | 4.8 V-8 | 5,300d          |
| 1500 4WD       | 4.8 V-8 | 6,300e          |
| 1500 4WD EC    | 4.8 V-8 | 5,000d          |
| 1500 4WD EC    | 4.8 V-8 | 6,000e          |
| 1500 4WD LB    | 4.3 V-6 | 3,800c          |
| 1500 4WD LB    | 4.3V-6  | 4,300d          |
| 1500 4WD LB    | 4.8 V-8 | 5,200d          |
| 1500 4WD LB    | 4.8 V-8 | 6,200e          |
| 1500 4WD LB EC | 4.8 V-8 | 4,800d          |
| 1500 4WD LB EC | 4.8 V-8 | 5,800e          |
| 2500 4WD EC    | 6.0 V-8 | 8,300d          |
| 2500 4WD EC    | 6.0 V-8 | 10,300e         |

## Sierra/Silverado Heavy Duty, Automatic or Manual Transmission, Conventional/Fifth-Wheel Towing

| Vehicle        | Engine | Tow Limit (lbs)<br>Conv/5th-Wheel |
|----------------|--------|-----------------------------------|
| 2500 EC        | 6.0 V8 | 10,300e                           |
| 2500 EC        | 8.1 V8 | 12,000d-e/13,900d; 15,900e        |
| 2500 EC        | 6.6 TD | 12,000d/15,800d                   |
| 2500 CC        | 6.0 V8 | 10,100e                           |
| 2500 CC        | 8.1 V8 | 12,000d-e/13,700d; 15,700e        |
| 2500 CC        | 6.6 TD | 12,000d/15,600d                   |
| 2500 LB        | 6.0 V8 | 10,500e                           |
| 2500 LB        | 8.1 V8 | 12,000d-e/14,300d; 16,300e        |
| 2500 LB        | 6.6 TD | 12,000d/16,200d                   |
| 2500 LB EC     | 6.0 V8 | 10,200e                           |
| 2500 LB EC     | 8.1 V8 | 12,000d-e/13,800d; 15,800e        |
| 2500 LB EC     | 6.6 TD | 12,000d/15,700d                   |
| 2500 LB CC     | 6.0 V8 | 10,000e                           |
| 2500 LB CC     | 8.1 V8 | 12,000d-e/13,500d; 15,500e        |
| 2500 LB CC     | 6.6 TD | 12,000d/15,400d                   |
| 3500 LB        | 6.0 V8 | 10,200e                           |
| 3500 LB        | 8.1 V8 | 12,000e/15,800e                   |
| 3500 LB        | 6.6 TD | 12,000d/15,600d                   |
| 3500 LB EC     | 6.0 V8 | 9,800e                            |
| 3500 LB EC     | 8.1 V8 | 12,000e/15,400e                   |
| 3500 LB EC     | 6.6 TD | 12,000d/15,300d                   |
| 3500 LB CC     | 6.0 V8 | 9,600e                            |
| 3500 LB CC     | 8.1 V8 | 12,000e/15,300e                   |
| 3500 LB CC     | 6.6 TD | 12,000d/15,100d                   |
| 2500 4WD EC    | 6.0 V8 | 10,200e                           |
| 2500 4WD EC    | 8.1 V8 | 12,000d-e/13,600d; 15,600e        |
| 2500 4WD EC    | 6.6 TD | 12,000d/15,500d                   |
| 2500 4WD CC    | 6.0 V8 | 9,800e                            |
| 2500 4WD CC    | 8.1 V8 | 12,000d-e/13,400d; 15,400e        |
| 2500 4WD CC    | 6.6 TD | 12,000d/15,300d                   |
| 2500 4WD LB    | 6.0 V8 | 10,200e                           |
| 2500 4WD LB    | 8.1 V8 | 12,000d-e/13,800d; 15,800e        |
| 2500 4WD LB    | 6.6 TD | 12,000d/15,700d                   |
| 2500 4WD LB EC | 6.0 V8 | 9,900e                            |
| 2500 4WD LB EC | 8.1 V8 | 12,000d-e/13,800d; 15,800e        |
| 2500 4WD LB EC | 6.6 TD | 12,000d/15,500d                   |
| 2500 4WD LB CC | 6.0 V8 | 9,700e                            |
| 2500 4WD LB CC | 8.1 V8 | 12,000d-e/13,200d; 15,200e        |
| 2500 4WD LB CC | 6.6 TD | 12,000d/15,100d                   |
| 3500 4WD LB    | 6.0 V8 | 9,900e                            |
| 3500 4WD LB    | 8.1 V8 | 12,000e/15,500e                   |
| 3500 4WD LB    | 6.6 TD | 12,000d/15,400d                   |
| 3500 4WD LB EC | 6.0 V8 | 9,500e                            |
| 3500 4WD LB EC | 8.1 V8 | 12,000e/15,100e                   |
| 3500 4WD LB EC | 6.6 TD | 12,000d/15,000d                   |
| 3500 4WD LB CC | 6.0 V8 | 9,300e                            |
| 3500 4WD LB CC | 8.1 V8 | 12,000e/14,900e                   |
| 3500 4WD LB CC | 6.6 TD | 12,000d/14,800d                   |

| Tahoe/Yukon/Suburban/Yukon XL |        |                 |
|-------------------------------|--------|-----------------|
| Vehicle                       | Engine | Tow Limit (lbs) |
| Tahoe/Yukon 1500              | 4.8 V8 | 5,700c          |
| Tahoe/Yukon 1500              | 4.8 V8 | 6,700d          |
| Tahoe/Yukon 1500              | 5.3 V8 | 6,700c          |
| Tahoe/Yukon 1500              | 5.3 V8 | 7,700d          |
| Suburban/Yukon XL 1500        | 5.3 V8 | 7,400d          |
| Suburban/Yukon XL 1500        | 5.3 V8 | 8,400e          |

| Vehicle                    | Engine | Tow Limit (lbs) |
|----------------------------|--------|-----------------|
| Tahoe/Yukon 1500 4WD       | 4.8 V8 | 6,400d          |
| Tahoe/Yukon 1500 4WD       | 4.8 V8 | 7,400e          |
| Tahoe/Yukon 1500 4WD       | 5.3 V8 | 7,400d          |
| Tahoe/Yukon 1500 4WD       | 5.3 V8 | 8,100e          |
| Yukon Denali 1500 AWD      | 6.0 V8 | 8,200d          |
| Suburban/Yukon XL 1500 4WD | 5.3 V8 | 7,300d          |
| Suburban/Yukon XL 1500 4WD | 5.3 V8 | 8,200e          |
| Yukon XL Denali 1500 AWD   | 6.0 V8 | 8,000d          |
| Suburban/Yukon XL 2500     | 6.0 V8 | 7,800d          |
| Suburban/Yukon XL 2500     | 6.0 V8 | 9,800e          |
| Suburban/Yukon XL 2500     | 8.1 V8 | 10,500d         |
| Suburban/Yukon XL 2500     | 8.1 V8 | 12,000e         |
| Suburban/Yukon XL 2500 4WD | 6.0 V8 | 7,500d          |
| Suburban/Yukon XL 2500 4WD | 6.0 V8 | 9,500e          |
| Suburban/Yukon XL 2500 4WD | 8.1 V8 | 10,100d         |
| Suburban/Yukon XL 2500 4WD | 8.1 V8 | 12,000e         |

TD=Turodiesel; 4WD= Four Wheel Drive; EC= Extended Cab; CC= Crew Cab; LB= Long Bed. A=3.08:1 axle ratio; B=3.23:1 axle ratio; C=3.42:1 axle ratio; D=3.73:1 axle ratio; E=4.10:1 axle ratio. Note: Weight distributing hitch and sway control required over 5,000 lbs of trailer weight on light duty models, 7,500 lbs on heavy duty models.

| Envoy/Trailblazer |         |                 |
|-------------------|---------|-----------------|
| Vehicle           | Engine  | Tow Limit (lbs) |
| 2WD               | 4.2 I-6 | 5,400a,b        |
| 2WD               | 4.2 I-6 | 5,900a,c        |
| 2WD               | 4.2 I-6 | 6,400a,d        |
| 2WD LWB           | 4.2 I-6 | 5,000a,b        |
| 2WD LWB           | 4.2 I-6 | 5,500a,c        |
| 2WD LWB           | 4.2 I-6 | 6,000a,d        |
| 4WD/AWD           | 4.2 I-6 | 5,200a,b        |
| 4WD/AWD           | 4.2 I-6 | 5,700a,c        |
| 4WD/AWD           | 4.2 I-6 | 6,200a,d        |
| 4WD/AWD LWB       | 4.2 I-6 | 4,800a,b        |
| 4WD/AWD LWB       | 4.2 I-6 | 5,300a,c        |
| 4WD/AWD LWB       | 4.2 I-6 | 5,800a,d        |

a=weight distributing hitch and sway control required over 4,000 lb. trailer weight; b=with 3.42:1 axle ratio; c=with 3.73:1 axle ratio; d=with 4.10:1 axle ratio; LWB=Long Wheel Base

## DAIMLERCHRYSLER

### Chrysler/Dodge Minivans

| Vehicle                   | Engine       | Tow Limit (lbs) |
|---------------------------|--------------|-----------------|
| Dodge Caravan             | 3.3, 3.8 V-6 | 3800i           |
| Dodge Grand Caravan (AWD) | 3.8 V-6      | 3,500           |
| Town & Country            | 3.3, 3.8 V-6 | 3,800i          |
| Town & Country (AWD)      | 3.8 V-6      | 3,500           |
| Voyager                   | 3.3 V-6      | 2000            |

### DODGE

| Vehicle | Engine  | Tow Limit (lbs) |
|---------|---------|-----------------|
| Dakota  | 2.5 I-4 | 2,200a,g        |
| Dakota  | 3.9 V-6 | 3,700a,e*       |
| Dakota  | 3.9 V-6 | 4,200a,f*       |
| Dakota  | 3.9 V-6 | 5,000d,f*       |
| Dakota  | 3.9 V-6 | 5,400d,g*       |
| Dakota  | 4.7 V-8 | 5,650a,f*       |
| Dakota  | 4.7 V-8 | 6,650a,g*       |
| Dakota  | 4.7 V-8 | 5,300d,f*       |

| Vehicle    | Engine  | Tow Limit (lbs) |
|------------|---------|-----------------|
| Dakota     | 4.7 V-8 | 6,600d,g*       |
| Dakota R/T | 5.9 V-8 | 2,000d,g        |

\*5,000 lb. GVWR models. 5,900 lb. GVWR models rated 100 lbs less.

| Vehicle    | Engine  | Tow Limit (lbs) |
|------------|---------|-----------------|
| Dakota 4WD | 3.9 V-6 | 3,950a,f*       |
| Dakota 4WD | 3.9 V-6 | 4,750a,g*       |
| Dakota 4WD | 3.9 V-6 | 5,100d,g*       |
| Dakota 4WD | 4.7 V-8 | 5,400a,f*       |
| Dakota 4WD | 4.7 V-8 | 6,400a,g*       |
| Dakota 4WD | 4.7 V-8 | 5,000d,f*       |
| Dakota 4WD | 4.7 V-8 | 6,300d,g*       |

\*5,400 lb. GVWR models. 5,900 lb. GVWR models rated 50-100 lbs less.

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| Dakota Club Cab     | 2.5 I-4 | 2,000a,g        |
| Dakota Club Cab     | 3.9 V-6 | 3,500a,e*       |
| Dakota Club Cab     | 3.9 V-6 | 4,000a,f*       |
| Dakota Club Cab     | 3.9 V-6 | 4,750d,f*       |
| Dakota Club Cab     | 3.9 V-6 | 5,150d,g*       |
| Dakota Club Cab     | 4.7 V-8 | 5,450a,f*       |
| Dakota Club Cab     | 4.7 V-8 | 6,450a,g*       |
| Dakota Club Cab     | 4.7 V-8 | 5,050d,f*       |
| Dakota Club Cab     | 4.7 V-8 | 6,350d,g*       |
| Dakota R/T Club Cab | 5.9 V-8 | 2,000d,g        |

\*5,350 lb. GVWR models. 5,900 lb. GVWR models rated 50-100 lbs less.

|                     |         |           |
|---------------------|---------|-----------|
| Dakota Club Cab 4WD | 3.9 V-6 | 3,750a,f* |
| Dakota Club Cab 4WD | 3.9 V-6 | 4,550a,g* |
| Dakota Club Cab 4WD | 3.9 V-6 | 4,900d,g* |
| Dakota Club Cab 4WD | 4.7 V-8 | 5,150a,f  |
| Dakota Club Cab 4WD | 4.7 V-8 | 6,150a,g  |
| Dakota Club Cab 4WD | 4.7 V-8 | 4,800d,f* |
| Dakota Club Cab 4WD | 4.7 V-8 | 6,100d,g* |

\*5,600 lb. GVWR models. 5,900 lb. GVWR models rated 50 lbs less.

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| Dakota Quad Cab     | 3.9 V-6 | 3,600a,f        |
| Dakota Quad Cab     | 3.9 V-6 | 4,400a,g        |
| Dakota Quad Cab     | 3.9 V-6 | 4,400d,f        |
| Dakota Quad Cab     | 3.9 V-6 | 4,800d,g        |
| Dakota Quad Cab     | 4.7 V-8 | 5,050a,f        |
| Dakota Quad Cab     | 4.7 V-8 | 6,050a,g        |
| Dakota Quad Cab     | 4.7 V-8 | 4,700d,f        |
| Dakota Quad Cab     | 4.7 V-8 | 6,000d,g        |
| Dakota Quad Cab     | 5.9 V-8 | 4,900d,f        |
| Dakota Quad Cab     | 5.9 V-8 | 6,200d,g        |
| Dakota Quad Cab 4WD | 3.9 V-6 | 3,350a,f        |
| Dakota Quad Cab 4WD | 3.9 V-6 | 4,150a,g        |
| Dakota Quad Cab 4WD | 3.9 V-6 | 4,150d,f        |
| Dakota Quad Cab 4WD | 3.9 V-6 | 4,550d,g        |
| Dakota Quad Cab 4WD | 4.7 V-8 | 4,800a,f        |
| Dakota Quad Cab 4WD | 4.7 V-8 | 5,800a,g        |
| Dakota Quad Cab 4WD | 4.7 V-8 | 4,750d,f        |
| Dakota Quad Cab 4WD | 4.7 V-8 | 5,750d,g        |
| Dakota Quad Cab 4WD | 5.9 V-8 | 4,650d,f        |
| Dakota Quad Cab 4WD | 5.9 V-8 | 5,950d,g        |
| Durango             | 4.7 V-8 | 4,650f          |
| Durango             | 4.7 V-8 | 5,950g          |
| Durango             | 5.9 V-8 | 5,850f          |

| Vehicle     | Engine  | Tow Limit (lbs) |
|-------------|---------|-----------------|
| Durango     | 5.9 V-8 | 7,550g          |
| Durango 4WD | 4.7 V-8 | 4,400f          |
| Durango 4WD | 4.7 V-8 | 5,700g          |
| Durango 4WD | 5.9 V-8 | 5,600f          |
| Durango 4WD | 5.9 V-8 | 7,300g          |

### Ram Van 1500

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| 109" Wheelbase      | 3.9 V-6 | 4,450c,f        |
| 109" Wheelbase      | 5.2 V-8 | 5,450d,g        |
| 109" Wheelbase      | 5.2 V-8 | 5,950d,h        |
| 127" Wheelbase      | 3.9 V-6 | 4,250c,f        |
| 127" Wheelbase      | 5.2 V-8 | 6,750d,f        |
| 127" Wheelbase      | 5.2 V-8 | 7,750d,g        |
| 127" Wheelbase      | 5.9 V-8 | 7,200d,f        |
| 127" Wheelbase      | 5.9 V-8 | 8,200d,g        |
| 127" Wheelbase Maxi | 3.9 V-6 | 4,150c,f        |
| 127" Wheelbase Maxi | 5.2 V-8 | 6,650d,f        |
| 127" Wheelbase Maxi | 5.2 V-8 | 7,650d,g        |
| 127" Wheelbase Maxi | 5.9 V-8 | 7,100d,f        |
| 127" Wheelbase Maxi | 5.9 V-8 | 8,100d,g        |

### Ram Van 2500

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| 127" Wheelbase      | 3.9 V-6 | 4,050c,g        |
| 127" Wheelbase      | 5.2 V-8 | 7,600d,f        |
| 127" Wheelbase      | 5.2 V-8 | 8,100d,g        |
| 127" Wheelbase      | 5.9 V-8 | 8,100d,g        |
| 127" Wheelbase      | 5.9 V-8 | 8,600d,h        |
| 127" Wheelbase Maxi | 5.2 V-8 | 7,450d,g        |
| 127" Wheelbase Maxi | 5.2 V-8 | 7,950d,h        |
| 127" Wheelbase Maxi | 5.9 V-8 | 7,900d,g        |
| 127" Wheelbase Maxi | 5.9 V-8 | 8,400d,h        |

### Ram Van 3500

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| 127" Wheelbase      | 5.2 V-8 | 7,550d,g        |
| 127" Wheelbase      | 5.2 V-8 | 8,050d,h        |
| 127" Wheelbase      | 5.9 V-8 | 8,050d,g        |
| 127" Wheelbase      | 5.9 V-8 | 8,550d,h        |
| 127" Wheelbase Maxi | 5.2 V-8 | 7,400d,g        |
| 127" Wheelbase Maxi | 5.2 V-8 | 7,900d,h        |
| 127" Wheelbase Maxi | 5.9 V-8 | 7,900d,g        |
| 127" Wheelbase Maxi | 5.9 V-8 | 8,400d,h        |

### Ram Wagon 1500

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| 109" Wheelbase | 3.9 V-6 | 4,050c,f        |
| 109" Wheelbase | 5.2 V-8 | 5,050d,f        |
| 109" Wheelbase | 5.2 V-8 | 5,550d,g        |

### Ram Wagon 2500

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| 127" Wheelbase | 5.2 V-8 | 7,200d,g        |
| 127" Wheelbase | 5.2 V-8 | 7,700d,h        |
| 127" Wheelbase | 5.9 V-8 | 7,650d,g        |
| 127" Wheelbase | 5.9 V-8 | 8,150d,h        |

| Ram Wagon 3500      |        |                 |
|---------------------|--------|-----------------|
| Vehicle             | Engine | Tow Limit (lbs) |
| 127" Wheelbase Maxi | 5.2 V8 | 6,750d,g        |
| 127" Wheelbase Maxi | 5.2 V8 | 7,250d,h        |
| 127" Wheelbase Maxi | 5.9 V8 | 7,250d,g        |
| 127" Wheelbase Maxi | 5.9 V8 | 7,750d,h        |

| Ram Truck 1500    |        |                 |
|-------------------|--------|-----------------|
| Vehicle           | Engine | Tow Limit (lbs) |
| 1500              | 3.7 V6 | 3,350a,f/g      |
| 1500              | 3.7 V6 | 3,800d,f/g      |
| 1500              | 4.7 V8 | 4,800a,f        |
| 1500              | 4.7 V8 | 5,800a,g        |
| 1500              | 4.7 V8 | 4,750a,g*       |
| 1500              | 4.7 V8 | 6,750d,f        |
| 1500              | 4.7 V8 | 7,750d,g        |
| 1500              | 4.7 V8 | 6,700d,g*       |
| 1500              | 5.9 V8 | 7,650d,f        |
| 1500              | 5.9 V8 | 8,650d,g        |
| 1500              | 5.9 V8 | 7,600d,g*       |
| 1500 4WD          | 4.7 V8 | 4,550a,f        |
| 1500 4WD          | 4.7 V8 | 5,550a,g        |
| 1500 4WD          | 4.7 V8 | 4,450a,g*       |
| 1500 4WD          | 4.7 V8 | 6,450d,f        |
| 1500 4WD          | 4.7 V8 | 7,450d,g        |
| 1500 4WD          | 4.7 V8 | 6,400d,g*       |
| 1500 4WD          | 5.9 V8 | 7,400d,f        |
| 1500 4WD          | 5.9 V8 | 8,400d,g        |
| 1500 4WD          | 5.9 V8 | 7,350d,g*       |
| 1500 Quad Cab     | 4.7 V8 | 4,450a,f        |
| 1500 Quad Cab     | 4.7 V8 | 5,450a,g        |
| 1500 Quad Cab     | 4.7 V8 | 4,400a,g*       |
| 1500 Quad Cab     | 4.7 V8 | 6,400d,f        |
| 1500 Quad Cab     | 4.7 V8 | 7,400d,g        |
| 1500 Quad Cab     | 4.7 V8 | 6,350d,g*       |
| 1500 Quad Cab     | 5.9 V8 | 7,350d,f        |
| 1500 Quad Cab     | 5.9 V8 | 8,350d,g        |
| 1500 Quad Cab     | 5.9 V8 | 7,300d,g*       |
| 1500 Quad Cab 4WD | 4.7 V8 | 4,200a,f        |
| 1500 Quad Cab 4WD | 4.7 V8 | 5,200a,g        |
| 1500 Quad Cab 4WD | 4.7 V8 | 4,150a,g*       |
| 1500 Quad Cab 4WD | 4.7 V8 | 6,150d,f        |
| 1500 Quad Cab 4WD | 4.7 V8 | 7,150d,g        |
| 1500 Quad Cab 4WD | 4.7 V8 | 6,100d,g*       |
| 1500 Quad Cab 4WD | 5.9 V8 | 7,100d,f        |
| 1500 Quad Cab 4WD | 5.9 V8 | 8,100d,g        |
| 1500 Quad Cab 4WD | 5.9 V8 | 7,000d,g*       |

**NOTE:** Short box ratings shown. Long box models are rated to tow 200 lbs less, most models. \*With optional twenty-inch wheel and tire Sport Group available on short box models only.

| Ram Truck 2500<br>Regular Cab, Longbed |           |                 |
|----------------------------------------|-----------|-----------------|
| Vehicle                                | Engine    | Tow Limit (lbs) |
| 2500                                   | 5.9 V8    | 8,750a,f/h      |
| 2500                                   | 5.9 V8    | 8,800d,f/h      |
| 2500                                   | 8.0 V-10  | 13,350a,f/h     |
| 2500                                   | 8.0 V-10  | 13,400d,f/h     |
| 2500                                   | 5.9 TD    | 14,100a,f/h     |
| 2500                                   | 5.9 TD    | 10,150d,f       |
| 2500                                   | 5.9 TD    | 12,150d,h       |
| 2500                                   | 5.9 TD HO | 13,950b,f/h     |
| 2500 4WD                               | 5.9 V8    | 8,350a,f/h      |

| Vehicle  | Engine    | Tow Limit (lbs) |
|----------|-----------|-----------------|
| 2500 4WD | 5.9 V8    | 8,400d,f/h      |
| 2500 4WD | 8.0 V-10  | 12,950a,f/h     |
| 2500 4WD | 8.0 V-10  | 12,950d,f/h     |
| 2500 4WD | 5.9 TD    | 13,600a,f/h     |
| 2500 4WD | 5.9 TD    | 9,650d,f        |
| 2500 4WD | 5.9 TD    | 11,650d,h       |
| 2500 4WD | 5.9 TD HO | 13,450b,f/h     |

| 2500 Quad Cab Shortbed |           |                 |
|------------------------|-----------|-----------------|
| Vehicle                | Engine    | Tow Limit (lbs) |
| 2500 Quad Cab          | 5.9 V8    | 8,500a,f/h      |
| 2500 Quad Cab          | 5.9 V8    | 8,550d,f/h      |
| 2500 Quad Cab          | 8.0 V-10  | 13,100a,f/h     |
| 2500 Quad Cab          | 8.0 V-10  | 13,150d,f/h     |
| 2500 Quad Cab          | 5.9 TD    | 13,800a,f/h     |
| 2500 Quad Cab          | 5.9 TD    | 9,900d,f        |
| 2500 Quad Cab          | 5.9 TD    | 11,900d,h       |
| 2500 Quad Cab          | 5.9 TD HO | 13,650b,f/h     |
| 2500 Quad Cab 4WD      | 5.9 V8    | 8,100a,f/h      |
| 2500 Quad Cab 4WD      | 5.9 V8    | 8,100d,f/h      |
| 2500 Quad Cab 4WD      | 8.0 V-10  | 12,700a,f/h     |
| 2500 Quad Cab 4WD      | 8.0 V-10  | 12,700d,f/h     |
| 2500 Quad Cab 4WD      | 5.9 TD    | 13,400a,f/h     |
| 2500 Quad Cab 4WD      | 5.9 TD    | 9,450d,f        |
| 2500 Quad Cab 4WD      | 5.9 TD    | 11,450d,h       |
| 2500 Quad Cab 4WD      | 5.9 TD HO | 13,250b,f/h     |

**NOTE:** Longbed models tow between 100-150 lbs less.

| Ram Truck 3500<br>Regular Cab, Longbed |           |                 |
|----------------------------------------|-----------|-----------------|
| Vehicle                                | Engine    | Tow Limit (lbs) |
| 3500                                   | 5.9 V8    | 9,350a,f/h      |
| 3500                                   | 5.9 V8    | 9,400d,f/h      |
| 3500                                   | 8.0 V-10  | 13,050a,f/h     |
| 3500                                   | 8.0 V-10  | 13,050d,f/h     |
| 3500                                   | 5.9 TD    | 13,750a,f/h     |
| 3500                                   | 5.9 TD    | 9,800d,f        |
| 3500                                   | 5.9 TD    | 12,800d,h       |
| 3500                                   | 5.9 TD HO | 13,600b,f       |
| 3500                                   | 5.9 TD HO | 15,100b,h       |
| 3500 4WD                               | 5.9 V8    | 8,900a,f/h      |
| 3500 4WD                               | 5.9 V8    | 8,950d,f/h      |
| 3500 4WD                               | 8.0 V-10  | 12,600a,f/h     |
| 3500 4WD                               | 8.0 V-10  | 12,650d,f/h     |
| 3500 4WD                               | 5.9 TD    | 13,300a,f/h     |
| 3500 4WD                               | 5.9 TD    | 9,350d,f        |
| 3500 4WD                               | 5.9 TD    | 12,350d,h       |
| 3500 4WD                               | 5.9 TD HO | 13,200b,f       |
| 3500 4WD                               | 5.9 TD HO | 14,700b,h       |

| 3500 Quad Cab |          |                 |
|---------------|----------|-----------------|
| Vehicle       | Engine   | Tow Limit (lbs) |
| 3500 Quad Cab | 5.9 V8   | 8,950a,f/h      |
| 3500 Quad Cab | 5.9 V8   | 9,000d,f/h      |
| 3500 Quad Cab | 8.0 V-10 | 12,650a,f/h     |
| 3500 Quad Cab | 8.0 V-10 | 12,650d,f/h     |
| 3500 Quad Cab | 5.9 TD   | 13,350a,f/h     |
| 3500 Quad Cab | 5.9 TD   | 9,400d,f        |
| 3500 Quad Cab | 5.9 TD   | 12,400d,h       |

| Vehicle           | Engine    | Tow Limit (lbs) |
|-------------------|-----------|-----------------|
| 3500 Quad Cab     | 5.9 TD HO | 13,200b,f       |
| 3500 Quad Cab     | 5.9 TD HO | 14,700b,h       |
| 3500 Quad Cab 4WD | 5.9 V-8   | 8,550a,f*/h     |
| 3500 Quad Cab 4WD | 5.9 V-8   | 8,600d,f/h      |
| 3500 Quad Cab 4WD | 8.0 V-10  | 12,200a,f/h     |
| 3500 Quad Cab 4WD | 8.0 V-10  | 12,250d,f/h     |
| 3500 Quad Cab 4WD | 5.9 TD    | 12,950a,f/h     |
| 3500 Quad Cab 4WD | 5.9 TD    | 9,000d,f        |
| 3500 Quad Cab 4WD | 5.9 TD    | 12,000d,h       |
| 3500 Quad Cab 4WD | 5.9 TD HO | 12,800b,f       |
| 3500 Quad Cab 4WD | 5.9 TD HO | 14,300b,h       |

\*3.55:1 ratio not available in California.

**NOTES:** A gooseneck or fifth-wheel hitch attached to the vehicle frame should be used if the trailer being towed weighs over 10,000 lbs or has more than 1,000 lbs tongue weight. Camper Special Group Package is recommended with gooseneck or fifth-wheel applications. Use an exhaust brake for all 3500 manual transmission applications with a trailer weight over 10,000 lbs

TD= Turbo Diesel; a=five-speed manual; b=six-speed manual; c=three-speed automatic; d=four-speed automatic; e=3.21 axle; f=3.55 axle; g=3.92 axle; h=4.10 axle; i=optional Trailer Preparation Group required

## FORD

### Econoline Van/Wagon

| Vehicle       | Engine   | Tow Limit (lbs)<br>Van/Wagon |
|---------------|----------|------------------------------|
| E-150         | 4.2 V-6  | 5,000c/4,700c                |
| E-150         | 4.6 V-8  | 6,400c/6,100c                |
| E-150         | 5.4 V-8  | 6,800c/6,500c                |
| E-250         | 4.2 V-6  | 5,100d/NA                    |
| E-250         | 4.2 V-6  | 5,500e/NA                    |
| E-250         | 5.4 V-8  | 7,400d/NA                    |
| E-250 NGV     | 5.4 V-8  | 6,800d/NA                    |
| E-250 Ext     | 4.2 V-6  | 5,000d/NA                    |
| E-250 Ext     | 4.2 V-6  | 5,400e/NA                    |
| E-250 Ext     | 5.4 V-8  | 7,300d/NA                    |
| E-250 NGV Ext | 5.4 V-8  | 7,300d/NA                    |
| E-350         | 5.4 V-8  | 6,300c/NA                    |
| E-350         | 5.4 V-8  | 7,300e/7,300d-e              |
| E-350 NGV     | 5.4 V-8  | 6,700e/6,200e                |
| E-350         | 6.8 V-10 | 9,200d/8,800d                |
| E-350         | 6.8 V-10 | 10,000e                      |
| E-350         | 7.3 TD   | 9,700c/9,400c                |
| E-350         | 7.3 TD   | 10,000e                      |
| E-350 Ext     | 5.4 V-8  | 6,200c/5,700c                |
| E-350 Ext     | 5.4 V-8  | 7,200e/6,700d-e              |
| E-350 NGV Ext | 5.4 V-8  | 6,600e/6,100e                |
| E-350 Ext.    | 6.8 V-10 | 9,000d/8,500d                |
| E-350 Ext.    | 6.8 V-10 | 10,000e                      |
| E-350 Ext     | 7.3 TD   | 9,600c/9,100c                |
| E-350 Ext     | 7.3 TD   | 10,000e                      |

### Escape/Excursion/Expedition

| Vehicle       | Engine   | Tow Limit (lbs) |
|---------------|----------|-----------------|
| Escape        | 3.0 V-6  | 3,500n          |
| Excursion     | 5.4 V-8  | 6,200d          |
| Excursion     | 6.8 V-10 | 10,100d         |
| Excursion     | 6.8 V-10 | 10,500j         |
| Excursion     | 7.3 TD   | 10,500d         |
| Excursion 4WD | 5.4 V-8  | 7,200e          |
| Excursion 4WD | 6.8 V-10 | 9,600d          |
| Excursion 4WD | 6.8 V-10 | 11,000j         |

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| Excursion 4WD  | 7.3 TD  | 11,000d         |
| Expedition     | 4.6 V-8 | 6,300c          |
| Expedition     | 5.4 V-8 | 6,700b          |
| Expedition     | 5.4 V-8 | 7,700c,g        |
| Expedition     | 5.4 V-8 | 8,200d,g        |
| Expedition 4WD | 4.6 V-8 | 6,000c,g        |
| Expedition 4WD | 4.6 V-8 | 5,500c,h        |
| Expedition 4WD | 5.4 V-8 | 6,400b          |
| Expedition 4WD | 5.4 V-8 | 7,400c,g        |
| Expedition 4WD | 5.4 V-8 | 6,900c,h        |
| Expedition 4WD | 5.4 V-8 | 7,900d,g,m      |
| Expedition 4WD | 5.4 V-8 | 7,400d,h,m      |

### Explorer Sport (2dr) and Sport Trac, Manual/Automatic Transmission

| Vehicle                 | Engine  | Tow Limit (lbs)<br>Manual/Auto |
|-------------------------|---------|--------------------------------|
| Explorer Sport          | 4.0 V-6 | 3,060/5,120                    |
| Explorer Sport 4WD      | 4.0 V-6 | 2,840/4,880                    |
| Explorer Sport Trac     | 4.0 V-6 | 2,740/5,300                    |
| Explorer Sport Trac 4WD | 4.0 V-6 | 2,480/5,040                    |

### Explorer 4-Door, 5-Speed Automatic

| Vehicle      | Engine  | Tow Limit (lbs) |
|--------------|---------|-----------------|
| Explorer     | 4.0 V-6 | 3,500c          |
| Explorer     | 4.0 V-6 | 5,940d          |
| Explorer     | 4.6 V-8 | 3,500c          |
| Explorer     | 4.6 V-8 | 7,300d          |
| Explorer 4WD | 4.0 V-6 | 3,500c          |
| Explorer 4WD | 4.0 V-6 | 5,500d          |
| Explorer 4WD | 4.0 V-6 | 3,500c          |
| Explorer 4WD | 4.6 V-8 | 7,000d          |

### Explorer 4-Door, 5-Speed Manual

| Vehicle      | Engine  | Tow Limit (lbs) |
|--------------|---------|-----------------|
| Explorer     | 4.0 V-6 | 2,700d          |
| Explorer 4WD | 4.0 V-6 | 2,500d          |

### F-150, Manual Transmission, Conventional Towing

| Vehicle         | Engine  | Tow Limit (lbs) |
|-----------------|---------|-----------------|
| Regular Cab     | 4.2 V-6 | 2,000a          |
| Regular Cab     | 4.2 V-6 | 3,500c          |
| Regular Cab     | 4.6 V-8 | 2,000a          |
| Regular Cab     | 4.6 V-8 | 2,900b          |
| Regular Cab     | 4.6 V-8 | 3,500c          |
| Regular Cab 4WD | 4.2 V-6 | 2,600b          |
| Regular Cab 4WD | 4.2 V-6 | 3,200c          |
| Regular Cab 4WD | 4.6 V-8 | 2,500b          |
| Regular Cab 4WD | 4.6 V-8 | 3,100c          |
| SuperCab        | 4.2 V-6 | 2,000a          |
| SuperCab        | 4.2 V-6 | 3,300c          |
| SuperCab        | 4.6 V-8 | 2,000a          |
| SuperCab        | 4.6 V-8 | 2,600b          |
| SuperCab        | 4.6 V-8 | 3,200c          |
| SuperCab 4WD    | 4.6 V-8 | 2,300b          |
| SuperCab 4WD    | 4.6 V-8 | 2,900c          |

**F-150, Automatic Transmission,  
Conventional/Fifth-Wheel Towing**

| Vehicle         | Engine  | Tow Limit (lbs)<br>Conv/5th-Wheel |
|-----------------|---------|-----------------------------------|
| Regular Cab     | 4.2 V-6 | 4,700b/NA                         |
| Regular Cab     | 4.2 V-6 | 5,700c/5,800c                     |
| Regular Cab     | 4.6 V-8 | 2,000a/NA                         |
| Regular Cab     | 4.6 V-8 | 6,200b/NA                         |
| Regular Cab     | 4.6 V-8 | 7,200c.g                          |
| Regular Cab     | 5.4 V-8 | 7,600b/NA                         |
| Regular Cab     | 5.4 V-8 | 8,600c.g                          |
| Regular Cab     | 5.4 V-8 | 8,800d/8,800d,o                   |
| Regular Cab NGV | 5.4 V-8 | 5,900d/NA                         |
| Regular Cab 4WD | 4.2 V-6 | 5,400c                            |
| Regular Cab 4WD | 4.6 V-8 | 5,800b/NA                         |
| Regular Cab 4WD | 4.6 V-8 | 6,800c.g/6,900c.g                 |
| Regular Cab 4WD | 4.6 V-8 | 6,300c,h/6,400c,h                 |
| Regular Cab 4WD | 5.4 V-8 | 7,200b/NA                         |
| Regular Cab 4WD | 5.4 V-8 | 7,700c,h/7,800c,h                 |
| Regular Cab 4WD | 5.4 V-8 | 8,400d/8,400d,o                   |
| SuperCab        | 4.2 V-6 | 4,500b/NA                         |
| SuperCab        | 4.2 V-6 | 5,500c                            |
| Super Cab       | 4.6 V-8 | 2,000a/NA                         |
| Super Cab       | 4.6 V-8 | 5,900b/NA                         |
| Super Cab       | 4.6 V-8 | 6,900c.g                          |
| SuperCab        | 5.4 V-8 | 7,300b/NA                         |
| SuperCab        | 5.4 V-8 | 8,300c.g                          |
| SuperCab        | 5.4 V-8 | 8,600d/8,600d,o; 8,600e,p         |
| SuperCab 4WD    | 4.6 V-8 | 5,600b/NA                         |
| SuperCab 4WD    | 4.6 V-8 | 6,600c.g                          |
| SuperCab 4WD    | 4.6 V-8 | 6,100c,h                          |
| SuperCab 4WD    | 5.4 V-8 | 7,000b/NA                         |
| SuperCab 4WD    | 5.4 V-8 | 8,000c.g                          |
| SuperCab 4WD    | 5.4 V-8 | 7,500c,h                          |
| SuperCab 4WD    | 5.4 V-8 | 8,200d/8,300d,o                   |
| Super Crew      | 4.6 V-8 | 6,600c.g/NA*                      |
| SuperCrew       | 5.4 V-8 | 8,000c.g/NA*                      |
| Super Crew 4WD  | 4.6 V-8 | 6,200c.g/NA*                      |
| Super Crew 4WD  | 4.6 V-8 | 6,100d,h/NA*                      |
| SuperCrew 4WD   | 5.4 V-8 | 7,600c.g/NA*                      |
| SuperCrew 4WD   | 5.4 V-8 | 7,100c,h/NA*                      |

**\*Note:** While the F-150 SuperCrew is capable of towing up to 8,000 lbs and the box will accept a fifth-wheel hitch, current fifth-wheel trailer designs are not compatible with SuperCrew. Any questions should be referred to the trailer dealer/manufacture.

**Super Duty F-250/F-350,  
Manual Transmission,  
Conventional/Fifth-Wheel Towing**

| Vehicle         | Engine   | Tow Limit (lbs)<br>Conv/5th-Wheel |
|-----------------|----------|-----------------------------------|
| Regular Cab     | 5.4 V-8  | 7,800d                            |
| Regular Cab     | 5.4 V-8  | 9,300e                            |
| Regular Cab     | 6.8 V-10 | 10,700d                           |
| Regular Cab     | 6.8 V-10 | 12,500j/14,200j                   |
| Regular Cab     | 7.3 TD   | 12,500d/13,700d                   |
| Regular Cab 4WD | 5.4 V-8  | 7,400d                            |
| Regular Cab 4WD | 5.4 V-8  | 8,900e                            |
| Regular Cab 4WD | 6.8 V-10 | 10,300d                           |
| Regular Cab 4WD | 6.8 V-10 | 12,500j/13,800j                   |
| Regular Cab 4WD | 7.3 TD   | 12,500d/13,300d                   |
| SuperCab        | 5.4 V-8  | 7,500d                            |
| SuperCab        | 5.4 V-8  | 9,000e                            |
| SuperCab        | 6.8 V-10 | 10,300d                           |

| Vehicle                | Engine   | Tow Limit (lbs)<br>Conv/5th-Wheel |
|------------------------|----------|-----------------------------------|
| SuperCab               | 6.8 V-10 | 12,500j/13,800j                   |
| SuperCab               | 7.3 TD   | 12,500d/13,400d                   |
| SuperCab 4WD           | 5.4 V-8  | 7,100d                            |
| SuperCab 4WD           | 5.4 V-8  | 8,600e                            |
| SuperCab 4WD           | 6.8 V-10 | 9,900d                            |
| SuperCab 4WD           | 6.8 V-10 | 12,500j/13,400j                   |
| SuperCab 4WD           | 7.3 TD   | 12,500d/13,000d                   |
| Crew Cab               | 5.4 V-8  | 7,200d                            |
| Crew Cab               | 5.4 V-8  | 8,700e                            |
| Crew Cab               | 6.8 V-10 | 10,100d                           |
| Crew Cab               | 6.8 V-10 | 12,500j/13,600j                   |
| Crew Cab               | 7.3 TD   | 12,500d/13,100d                   |
| Crew Cab 4WD           | 5.4 V-8  | 6,900d                            |
| Crew Cab 4WD           | 5.4 V-8  | 8,400e                            |
| Crew Cab 4WD           | 6.8 V-10 | 9,700d                            |
| Crew Cab 4WD           | 6.8 V-10 | 12,500j/13,200j                   |
| Crew Cab 4WD           | 7.3 TD   | 12,500d/12,800d                   |
| F-350 DRW              | 5.4 V-8  | 7,600d                            |
| F-350 DRW              | 5.4 V-8  | 9,100e                            |
| F-350 DRW              | 6.8 V-10 | 10,300d                           |
| F-350 DRW              | 6.8 V-10 | 12,500j/13,800j                   |
| F-350 DRW              | 7.3 TD   | 12,500d-e/13,400d-e               |
| F-350 4WD DRW          | 5.4 V-8  | 7,100d                            |
| F-350 4WD DRW          | 5.4 V-8  | 8,600e                            |
| F-350 4WD DRW          | 6.8 V-10 | 9,900d                            |
| F-350 4WD DRW          | 6.8 V-10 | 12,500j/13,400j                   |
| F-350 4WD DRW          | 7.3 TD   | 12,500d-e/12,900d-e               |
| F-350 SuperCab DRW     | 5.4 V-8  | 7,200d                            |
| F-350 SuperCab DRW     | 5.4 V-8  | 8,700e                            |
| F-350 SuperCab DRW     | 6.8 V-10 | 10,000d                           |
| F-350 SuperCab DRW     | 6.8 V-10 | 12,500j/13,500j                   |
| F-350 SuperCab DRW     | 7.3 TD   | 12,500d-e/13,100d-e               |
| F-350 SuperCab 4WD DRW | 5.4 V-8  | 6,900d                            |
| F-350 SuperCab 4WD DRW | 5.4 V-8  | 8,400e                            |
| F-350 SuperCab 4WD DRW | 6.8 V-10 | 9,700d                            |
| F-350 SuperCab 4WD DRW | 6.8 V-10 | 12,500j/13,200j                   |
| F-350 SuperCab 4WD DRW | 7.3 TD   | 12,500d-e/12,700d-e               |
| F-350 Crew Cab DRW     | 6.8 V-10 | 9,800d                            |
| F-350 Crew Cab DRW     | 6.8 V-10 | 12,500j/13,300j                   |
| F-350 Crew Cab DRW     | 7.3 TD   | 12,500d-e/12,800d-e               |
| F-350 Crew Cab 4WD DRW | 6.8 V-10 | 9,300d                            |
| F-350 Crew Cab 4WD DRW | 6.8 V-10 | 12,500j/12,800j                   |
| F-350 Crew Cab 4WD DRW | 7.3 TD   | 12,400d-e                         |

**Super Duty F-250/F-350,  
Automatic Transmission,  
Conventional/Fifth-Wheel Towing**

| Vehicle         | Engine   | Tow Limit (lbs)<br>Conv/5th-Wheel |
|-----------------|----------|-----------------------------------|
| Regular Cab     | 5.4 V-8  | 7,900d                            |
| Regular Cab     | 5.4 V-8  | 9,400e                            |
| Regular Cab     | 6.8 V-10 | 11,200d                           |
| Regular Cab     | 6.8 V-10 | 12,500j/14,200j                   |
| Regular Cab     | 7.3 TD   | 12,500d/13,800d                   |
| Regular Cab 4WD | 5.4 V-8  | 7,500d                            |
| Regular Cab 4WD | 5.4 V-8  | 9,000e                            |
| Regular Cab 4WD | 6.8 V-10 | 10,800d                           |
| Regular Cab 4WD | 6.8 V-10 | 12,500j/13,800j                   |
| Regular Cab 4WD | 7.3 TD   | 12,500d/13,400d                   |
| SuperCab        | 5.4 V-8  | 7,500d                            |



| Vehicle                | Engine   | Tow Limit (lbs)<br>Conv/5th-Wheel |
|------------------------|----------|-----------------------------------|
| SuperCab               | 5.4 V-8  | 9,000e                            |
| SuperCab               | 6.8 V-10 | 10,900d                           |
| SuperCab               | 6.8 V-10 | 12,500j/13,900j                   |
| SuperCab               | 7.3 TD   | 12,500d/13,400d                   |
| SuperCab 4WD           | 5.4 V-8  | 7,100d                            |
| SuperCab 4WD           | 5.4 V-8  | 8,600e                            |
| SuperCab 4WD           | 6.8 V-10 | 10,500d                           |
| SuperCab 4WD           | 6.8 V-10 | 12,500j/13,500j                   |
| SuperCab 4WD           | 7.3 TD   | 12,500d/13,000d                   |
| Crew Cab               | 5.4 V-8  | 7,300d                            |
| Crew Cab               | 5.4 V-8  | 8,800e                            |
| Crew Cab               | 6.8 V-10 | 10,600d                           |
| Crew Cab               | 6.8 V-10 | 12,500j/13,600j                   |
| Crew Cab               | 7.3 TD   | 12,500d/13,200d                   |
| Crew Cab 4WD           | 5.4 V-8  | 6,900d                            |
| Crew Cab 4WD           | 5.4 V-8  | 8,400e                            |
| Crew Cab 4WD           | 6.8 V-10 | 10,300d                           |
| Crew Cab 4WD           | 6.8 V-10 | 12,500j/13,300j                   |
| Crew Cab 4WD           | 7.3 TD   | 12,500d/12,800d                   |
| F-350 DRW              | 5.4 V-8  | 7,600d                            |
| F-350 DRW              | 5.4 V-8  | 9,100e                            |
| F-350 DRW              | 6.8 V-10 | 10,900d                           |
| F-350 DRW              | 6.8 V-10 | 12,500j/13,900j                   |
| F-350 DRW              | 7.3 TD   | 12,500d-e/13,400d-e               |
| F-350 4WD DRW          | 5.4 V-8  | 7,200d                            |
| F-350 4WD DRW          | 5.4 V-8  | 8,700e                            |
| F-350 4WD DRW          | 6.8 V-10 | 10,500d                           |
| F-350 4WD DRW          | 6.8 V-10 | 12,500j/13,500j                   |
| F-350 4WD DRW          | 7.3 TD   | 12,500d-e/13,000d-e               |
| F-350 SuperCab DRW     | 5.4 V-8  | 7,200d                            |
| F-350 SuperCab DRW     | 5.4 V-8  | 8,700e                            |
| F-350 SuperCab DRW     | 6.8 V-10 | 10,500d                           |
| F-350 SuperCab DRW     | 6.8 V-10 | 12,500j/13,500j                   |
| F-350 SuperCab DRW     | 7.3 TD   | 12,500d-e/13,100d-e               |
| F-350 SuperCab 4WD DRW | 5.4 V-8  | 6,900d                            |
| F-350 SuperCab 4WD DRW | 5.4 V-8  | 8,600e/8,400e                     |
| F-350 SuperCab DRW     | 6.8 V-10 | 10,200d                           |
| F-350 SuperCab DRW     | 6.8 V-10 | 12,500j/13,200j                   |
| F-350 SuperCab 4WD DRW | 7.3 TD   | 12,500d-e/12,800d-e               |
| F-350 Crew Cab DRW     | 6.8 V-10 | 10,300d                           |
| F-350 Crew Cab DRW     | 6.8 V-10 | 12,500j/13,300j                   |
| F-350 Crew Cab DRW     | 7.3 TD   | 12,500d-e/12,900d-e               |
| F-350 Crew Cab 4WD DRW | 6.8 V-10 | 9,900d                            |
| F-350 Crew Cab 4WD DRW | 6.8 V-10 | 12,500j/12,900j                   |
| F-350 Crew Cab 4WD DRW | 7.3 TD   | 12,500d-e/12,400d-e               |

**NOTE:** For F-250/350 single rear wheel models, F-350 weights are shown; F-250 trailer weights may be 100-200 lbs greater. Check with your dealer for more details.

### Super Duty F-350/450/550 Chassis Cab, Manual/Automatic Transmission, Fifth-Wheel Towing

| Vehicle   | Engine   | Tow Limit (lbs)<br>Manual/Auto |
|-----------|----------|--------------------------------|
| F-350     | 5.4 V-8  | 7,200d/7300d                   |
| F-350     | 5.4 V-8  | 8,700e/8,800e                  |
| F-350     | 6.8 V-10 | 10,100d/10,600d                |
| F-350     | 7.3 TD   | 13,100d/13,200d                |
| F-350 4WD | 5.4 V-8  | 6,800d                         |
| F-350 4WD | 5.4 V-8  | 8,300e                         |

| Vehicle           | Engine   | Tow Limit (lbs)<br>Manual/Auto |
|-------------------|----------|--------------------------------|
| F-350 4WD         | 6.8 V-10 | 9,700d/10,200d                 |
| F-350 4WD         | 7.3 TD   | 12,700d                        |
| F-350 DRW         | 5.4 V-8  | 6,900d/7,000d                  |
| F-350 DRW         | 5.4 V-8  | 8,400e/8,500e                  |
| F-350 DRW         | 6.8 V-10 | 9,700d/10,300d                 |
| F-350 DRW         | 6.8 V-10 | 13,200j/13,300j                |
| F-350 DRW         | 7.3 TD   | 12,800d/e                      |
| F-350 4WD DRW     | 5.4 V-8  | 6,400d/6,500d                  |
| F-350 4WD DRW     | 5.4 V-8  | 7,900e/8,000e                  |
| F-350 4WD DRW     | 6.8 V-10 | 9,300d/9,800d                  |
| F-350 4WD DRW     | 6.8 V-10 | 12,800j                        |
| F-350 4WD DRW     | 7.3 TD   | 12,300d/e                      |
| F-350 SCC         | 5.4 V-8  | 6,900d                         |
| F-350 SCC         | 5.4 V-8  | 8,400e                         |
| F-350 SCC         | 6.8 V-10 | 9,700d/10,200d                 |
| F-350 SCC         | 7.3 TD   | 12,800d                        |
| F-350 4WD SCC     | 5.4 V-8  | 6,400d/6,500d                  |
| F-350 4WD SCC     | 5.4 V-8  | 7,900e/8,000e                  |
| F-350 4WD SCC     | 6.8 V-10 | 9,300d/9,800d                  |
| F-350 4WD SCC     | 7.3 TD   | 12,300d/12,400d                |
| F-350 SCC DRW     | 6.8 V-10 | 9,400d/9,900d                  |
| F-350 SCC DRW     | 6.8 V-10 | 12,900j                        |
| F-350 SCC DRW     | 7.3 TD   | 12,400d/e                      |
| F-350 SCC 4WD DRW | 6.8 V-10 | 9,000d/9,500d                  |
| F-350 SCC 4WD DRW | 6.8 V-10 | 12,500j                        |
| F-350 SCC 4WD DRW | 7.3 TD   | 12,000d/e                      |
| F-350 CCC         | 5.4 V-8  | 6,700d                         |
| F-350 CCC         | 5.4 V-8  | 8,200e                         |
| F-350 CCC         | 6.8 V-10 | 9,500d/10,000d                 |
| F-350 CCC         | 7.3 TD   | 12,600d                        |
| F-350 CCC 4WD     | 5.4 V-8  | 6,200d/6,300d                  |
| F-350 CCC 4WD     | 5.4 V-8  | 7,700e/7,800e                  |
| F-350 CCC 4WD     | 6.8 V-10 | 9,100d/9,600d                  |
| F-350 CCC 4WD     | 7.3 TD   | 12,100d/12,200d                |
| F-350 CCC DRW     | 6.8 V-10 | 9,200d/9,700d                  |
| F-350 CCC DRW     | 6.8 V-10 | 12,700j                        |
| F-350 CCC DRW     | 7.3 TD   | 12,200d/e/12,300d/e            |
| F-350 CCC 4WD DRW | 6.8 V-10 | 8,700d/9,300d                  |
| F-350 CCC 4WD DRW | 6.8 V-10 | 12,200j/12,300j                |
| F-350 CCC 4WD DRW | 7.3 TD   | 11,800d/e                      |
| F-450 DRW         | 6.8 V-10 | 14,500k-l/16,600k; 18,600l     |
| F-450 DRW         | 7.3 TD   | 18,100j-k                      |
| F-450 4WD DRW     | 6.8 V-10 | 14,200k-l/16,300k; 18,300l     |
| F-450 4WD DRW     | 7.3 TD   | 17,800j-k                      |
| F-450 SCC DRW     | 6.8 V-10 | 14,200k-l/16,200k; 18,200l     |
| F-450 SCC DRW     | 7.3 TD   | 17,700j-k/17,800j-k            |
| F-450 SCC 4WD DRW | 6.8 V-10 | 13,800k-l/15,800k; 17,800l     |
| F-450 SCC 4WD DRW | 7.3 TD   | 17,300j-k/17,400j-k            |
| F-450 CCC DRW     | 6.8 V-10 | 14,000k-l/16,000k; 18,000l     |
| F-450 CCC DRW     | 7.3 TD   | 17,500j-k                      |
| F-450 CCC 4WD DRW | 6.8 V-10 | 13,700k-l/15,700k; 17,700l     |
| F-450 CCC 4WD DRW | 7.3 TD   | 17,200j-k                      |
| F-550 DRW         | 6.8 V-10 | NA/16,500k                     |
| F-550 DRW         | 6.8 V-10 | NA/18,500l                     |
| F-550 DRW         | 7.3 TD   | 18,000k                        |
| F-550 4WD DRW     | 6.8 V-10 | NA/16,200k                     |
| F-550 4WD DRW     | 6.8 V-10 | NA/18,200l                     |
| F-550 4WD DRW     | 7.3 TD   | 17,700k                        |
| F-550 SCC DRW     | 6.8 V-10 | NA/16,200k                     |
| F-550 SCC DRW     | 6.8 V-10 | NA/18,200l                     |
| F-550 SCC DRW     | 7.3 TD   | 17,700k                        |

| Vehicle           | Engine   | Tow Limit (lbs)<br>Manual/Auto |
|-------------------|----------|--------------------------------|
| F-550 SCC 4WD DRW | 6.8 V-10 | NA/15,700k                     |
| F-550 SCC 4WD DRW | 6.8 V-10 | NA/17,700l                     |
| F-550 SCC 4WD DRW | 7.3 TD   | 17,200k/17,300k                |
| F-550 CCC DRW     | 6.8 V-10 | NA/15,900k                     |
| F-550 CCC DRW     | 6.8 V-10 | NA/17,900l                     |
| F-550 CCC DRW     | 7.3 TD   | 17,400k/17,500k; 21,500k,f     |
| F-550 CCC 4WD DRW | 6.8 V-10 | NA/15,600k                     |
| F-550 CCC 4WD DRW | 6.8 V-10 | NA/17,600l                     |
| F-550 CCC 4WD DRW | 7.3 TD   | 17,100k                        |

**NOTE:** F-450/550 weights shown are for 141-inch wheelbase Regular Cab or 176-inch wheelbase Crew Cab models. For 165, 189, 200 and 201-inch wheelbase models, weights may be somewhat less (usually not more than 400 lbs). Check with your dealer for more details.

### Super Duty F-650/750, All Models/Powertrains

| Model             | Max GVWR  | Max GCWR        |
|-------------------|-----------|-----------------|
| F-650, All Models | 26,000lbs | 40,000lbs GCWR* |
| F-750 All Models  | 30,000lbs | 45,000lbs GCWR* |
| F-750 All Models  | 33,000lbs | 60,000lbs GCWR* |

\*To determine maximum trailer weight, subtract your vehicle's GVWR from the maximum GCWR.

### Ranger, Manual Transmission

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| Ranger              | 3.0 V-6 | 2,640d          |
| Ranger              | 3.0 V-6 | 2,540d*         |
| Ranger              | 4.0 V-6 | 3,560c          |
| Ranger              | 4.0 V-6 | 3,460c*         |
| Ranger 4WD          | 3.0 V-6 | 2,360d/e        |
| Ranger 4WD          | 4.0 V-6 | 3,300d/e        |
| Ranger SuperCab     | 3.0 V-6 | 2,480d          |
| Ranger SuperCab     | 3.0 V-6 | 2,320d*         |
| Ranger SuperCab     | 4.0 V-6 | 3,400c          |
| Ranger SuperCab     | 4.0 V-6 | 3,260c*         |
| Ranger SuperCab 4WD | 3.0 V-6 | 2,200d/e        |
| Ranger SuperCab 4WD | 4.0 V-6 | 3,140d/e***     |

### Ranger, Automatic Transmission

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| Ranger              | 2.3 I-4 | 2,240e          |
| Ranger              | 3.0 V-6 | 4,100d          |
| Ranger              | 3.0 V-6 | 4,000d*         |
| Ranger              | 4.0 V-6 | 6,020c          |
| Ranger              | 4.0 V-6 | 5,940c*         |
| Ranger 4WD          | 3.0 V-6 | 3,820d/e        |
| Ranger 4WD          | 4.0 V-6 | 5,760d/e        |
| Ranger SuperCab     | 3.0 V-6 | 3,940d          |
| Ranger SuperCab     | 3.0 V-6 | 3,780d*         |
| Ranger SuperCab     | 4.0 V-6 | 5,860c          |
| Ranger SuperCab     | 4.0 V-6 | 5,720c*         |
| Ranger SuperCab 4WD | 3.0 V-6 | 3,680d/e        |
| Ranger SuperCab 4WD | 4.0 V-6 | 5,600d/e**      |

\*Ranger Edge only; \*\*5,200 lbs with FX4; \*\*\*2,740 lbs with FX4.

### Windstar

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| Windstar Van   | 3.8 V-6 | 2,000           |
| Windstar Wagon | 3.8 V-6 | 2,000           |

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| Windstar Wagon | 3.8 V-6 | 3,500f          |

TD = Turbodiesel; Ext=Extended Cab; NGV=Natural Gas Vehicle; DRW=Dual Rear Wheels; SCC=Super Chassis Cab; CCC=Crew Chassis Cab; a= 3.08:1 axle ratio; b= 3.31:1 axle ratio; c= 3.55:1 axle ratio; d= 3.73:1 axle ratio; e= 4.09/4.10:1 axle ratio; f=Must be equipped with heavy-duty towing package; g=With 16 or 17-inch tires; h=With 17-inch tires; i= 3.27:1 axle ratio; j= 4.30:1 axle ratio; k= 4.88:1 axle ratio; l= 5.38:1 axle ratio; m=Available in high-altitude areas only; n=With Class II trailer towing package. Rating is 2,000 without; o=Available with 7700 Payload Group A only; p=Available with 7700 Payload Group B only.

## HONDA

| Vehicle  | Engine  | Tow Limit (lbs) |
|----------|---------|-----------------|
| Odyssey  | 3.5 V-6 | 3,500a,b        |
| Passport | 3.2 V-6 | 4,500c          |

a=With transmission fluid and power steering fluid coolers and two occupants. Deduct 150 pounds per passenger up to seven passengers.; b=Without transmission fluid/power steering fluid coolers; 2,000 pounds maximum with two occupants.; c=requires load-leveling hitch.

## HYUNDAI

| Vehicle      | Engine  | Tow Limit (lbs) |
|--------------|---------|-----------------|
| Santa Fe 2WD | 2.7 V-6 | 2,700a          |
| Santa Fe 4WD | 2.7 V-6 | 2,200a          |

a=Trailer must be equipped with brakes

## ISUZU

| Vehicle           | Engine      | Tow Limit (lbs) |
|-------------------|-------------|-----------------|
| Rodeo/Rodeo Sport | 2.2/2.6 I-4 | 2,500           |
| Rodeo Sport       | 3.2 V-6     | 4,500a          |
| Rodeo             | 3.2 V-6     | 4,500a          |
| Trooper           | 3.5 V-6     | 5,000a          |
| Axiom             | 3.5 V-6     | 4,500a          |

a= trailer brakes required on any trailer above 3500 lbs

## JEEP

| Vehicle        | Engine  | Tow Limit (lbs) |
|----------------|---------|-----------------|
| Grand Cherokee | 4.0 I-6 | 5,000b          |
| Grand Cherokee | 4.7 V-8 | 6,500b          |
| Liberty        | 2.4 I-4 | 2,000           |
| Liberty        | 3.7 V-6 | 5,000b,c        |
| Wrangler       | 2.5 I-4 | 2,000a          |
| Wrangler       | 4.0 I-6 | 2,000           |

**NOTE:** Trailer brakes required on all trailers weighing more than

1,000 pounds; a=Wrangler rating is 1,000 pounds with automatic transmission; b=Requires trailer towing package; c=Manual transmission version tows 1,500 lbs less.

## KIA

| Vehicle             | Engine  | Tow Limit (lbs) |
|---------------------|---------|-----------------|
| Sportage All Models | 2.0 I-4 | 2,000           |
| Sedona              | 3.5 V-6 | 3,500           |

## LAND ROVER

| Vehicle              | Engine  | Tow Limit (lbs) |
|----------------------|---------|-----------------|
| Discovery, Series II | All     | 5,500a,b*       |
| Range Rover          | All     | 6,500a,b*       |
| Freelander           | 2.5 V-6 | 2,500a          |

a=Maximum trailer weight without brakes is 1,650 pounds; b=Off-road maximum is 2,200 pounds; \*Can tow up to 7,700 lbs in low range

## LEXUS

| Vehicle | Engine  | Tow Limit (lbs) |
|---------|---------|-----------------|
| LX 470  | 4.7 V-8 | 6,500           |
| RX 300  | 3.0 V-6 | 3,500           |

## LINCOLN

| Vehicle   | Engine  | Tow Limit (lbs) |
|-----------|---------|-----------------|
| Blackwood | 5.4 V-8 | 8,700a,b        |
| Navigator | 5.4 V-8 | 8,800a,b        |

a=Requires optional Class III/IV Trailer Tow Package with load-equalizing hitch; b=4WD tow rating is 8,000 pounds.

## MAZDA

| Vehicle   | Engine  | Tow Limit (lbs) |
|-----------|---------|-----------------|
| B2500     | 2.5 I-4 | 2,240a,e        |
| B3000     | 3.0 V-6 | 4,000a,d,e      |
| B3000 4WD | 3.0 V-6 | 4,360a,d,e      |
| B4000     | 4.0 V-6 | 5,900a,c,d,e    |
| B4000 4WD | 4.0 V-6 | 5,700a,c,d      |
| MPV       | ***     | ***             |
| Tribute   | 3.0 V-6 | 3,500b          |

a=Requires automatic transmission; rating lower with manual transmission; b=Requires trailer-towing package; c=Requires special axle ratio and trailer-towing package; d=Requires load-equalizing hitch for more than 2,000 pounds; e=Cab Plus rating lower; \*\*\*No information available on this model at press time.

## MERCEDES-BENZ

| Vehicle  | Engine  | Tow Limit (lbs) |
|----------|---------|-----------------|
| G-500    | 5.0 V-8 | 7,000*          |
| ML 320   | 3.2 V-6 | 5,000           |
| ML 430   | 4.3 V-8 | 5,000           |
| ML55 AMG | 5.5 V-8 | 5,000           |

\*Late availability.

## MERCURY

| Vehicle         | Engine  | Tow Limit (lbs) |
|-----------------|---------|-----------------|
| Mountaineer 4X2 | 4.0 V-6 | 5,700b          |
| Mountaineer 4X4 | 4.0 V-6 | 5,460b,c        |
| Mountaineer 4X2 | 4.6 V-8 | 7,300b          |
| Mountaineer AWD | 4.6 V-8 | 7,060b,c        |
| Villager        | 3.3 V-6 | 2,000a          |
| Villager        | 3.3 V-6 | 3,500b          |

a=Class I load-carrying type/weight-equalizing hitch; b=Requires optional class II towing package; c=Requires Class IV load-equalizing hitch option and 3.73 gear ratio (standard on V8)

## MITSUBISHI

| Vehicle                    | Engine  | Tow Limit (lbs) |
|----------------------------|---------|-----------------|
| Montero Limited, XLS       | 3.5 V-6 | 5,000a          |
| Montero Sport ES, LS       | 3.0 V-6 | 5,000a          |
| Montero Sport XLS, Limited | 3.5 V-6 | 5,000a          |

a=Tow rating with trailer brakes; 1,500 pounds maximum rating without.

## NISSAN

| Vehicle                 | Engine  | Tow Limit (lbs) |
|-------------------------|---------|-----------------|
| Pathfinder/Infinity QX4 | 3.5 V-6 | 5,000a/5,000    |

| Vehicle  | Engine     | Tow Limit (lbs) |
|----------|------------|-----------------|
| Frontier | 2.4 I-4    | 3,500b,c        |
| Frontier | 3.3 V-6    | 5,000a          |
| Frontier | 3.3 V-6 SC | 5,000a          |
| Xterra   | 2.4 I-4    | 3,500           |
| Xterra   | 3.3 V-6    | 5,000a          |
| Xterra   | 3.3 V-6 SC | 5,000a          |
| Quest    | 3.3 V-6    | 3,500           |

a=Rating is 3,500 pounds with manual transmission; =Requires manual transmission; c=Rating is 2,000 lbs with an automatic transmission; SC=Super Charged

## OLDSMOBILE

| Vehicle         | Engine  | Tow Limit (lbs) |
|-----------------|---------|-----------------|
| Bravada 2WD     | 4.2 I-6 | 5,800a,b        |
| Bravada 2WD     | 4.2 I-6 | 6,300a,c        |
| Bravada 4WD/AWD | 4.2 I-6 | 5,600a,b        |
| Bravada 4WD/AWD | 4.2 I-6 | 6,100a,c        |
| Silhouette      | 3.4 V-6 | 3,500d          |

a=weight distributing hitch and sway control required over 4,000 lb. trailer weight; b= 3.73:1 axle ratio; c= 4.10:1 axle ratio; d=requires towing package

## PONTIAC

| Vehicle | Engine  | Tow Limit (lbs) |
|---------|---------|-----------------|
| Aztek   | 3.4 V-6 | 3500a           |
| Montana | 3.4 V-6 | 3,500a          |

a=Requires towing package.

## SATURN

| Vehicle | Engine  | Tow Limit (lbs) |
|---------|---------|-----------------|
| VUE AWD | 3.0 V-6 | 2,500 lbs       |

## SUBARU

| Vehicle                 | Engine       | Tow Limit (lbs) |
|-------------------------|--------------|-----------------|
| Legacy/Outback/Forester | 2.5 SOHC I-4 | 2,000a          |

a=Trailer brakes required. Maximum hitch weight 200 pounds.

## TOYOTA

| Vehicle                     | Engine    | Tow Limit (lbs) |
|-----------------------------|-----------|-----------------|
| 4Runner                     | 3.4 V-6   | 5,000           |
| Land Cruiser                | 4.7 V-8   | 6,500           |
| Sienna                      | 3.0 V-6   | 3,500*          |
| Tacoma                      | All I-4   | 3,500           |
| Tacoma                      | 3.4 V-6   | 5,000*          |
| S-Runner                    | 3.4 V-6   | 3,500           |
| Sequoia                     | 4.7 V-8   | 6,500           |
| Sequoia 4WD                 | 4.7 V-8   | 6,200           |
| Highlander                  | All I-4   | 3,000*          |
| Highlander                  | 3.0 V-6   | 3,500*          |
| Tundra 4x2 B-Cab            | 3.4 V-6 M | 5,250           |
| Tundra 4x2 B-Cab            | 3.4 V-6 A | 5,200           |
| Tundra 4x2 C-Cab            | 3.4 V-6 M | 4,950           |
| Tundra 4x2 C-Cab            | 3.4 V-6 A | 4,900           |
| Tundra 4x4 C-Cab            | 3.4 V-6 M | 5,000           |
| Tundra 4x4 C-Cab            | 3.4 V-6 A | 4,950           |
| Tundra 4x2 C-Cab (SR5, LTD) | 4.7 V-8   | 7,200           |
| Tundra 4x4 B-Cab            | 4.7 V-8   | 7,200           |
| Tundra 4x4 C-Cab (SR5, LTD) | 4.7 V-8   | 7,100           |

M= Manual Transmission; A= Automatic Transmission; All vehicles tongue weight is 10% of Maximum Towing Capacity; \*Optional towing package required.